




Marici 195 Specular



Ronde LED downlight met een lage inbouwhoogte. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<21). Gesatineerde PMMA afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (>68,0°) en hoge efficiency (max 147lm/w) met CRI>80. Wit gelakte (RAL 9003) aluminium behuizing. Wordt geleverd inclusief externe driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with shallow build-in height. High gloss aluminium reflector (99,9%) (UGR<21) with specular finish. Extra wide beam angle (>68,0°) and high efficiency (max 147lm/w) with CRI>80. Satinated PMMA diffuser for high comfort. White painted aluminium die cast body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including external driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <3. Fast and easy mounting with springs. Five years warranty.



Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali
9w	3000k	1265	250	1,3	1/3	62020W.00	62020W.01	62020W.02
12w	3000k	1715	350	1,3	1/3	62006W.00	62006W.01	62006W.02
18w	3000k	2365	500	1,3	1/3	62017W.00	62017W.01	62017W.02
25w	3000k	3175	700	1,3	1/3	62010W.00	62010W.01	62010W.02
33w	3000k	3930	900	1,3	1/3	62015W.00	62015W.01	62015W.02
39w	3000k	4465	1050	1,3	1/3	62013W.00	62013W.01	62013W.02
9w	4000k	1330	250	1,3	1/3	62021W.00	62021W.01	62021W.02
12w	4000k	1810	350	1,3	1/3	62007W.00	62007W.01	62007W.02
18w	4000k	2480	500	1,3	1/3	62018W.00	62018W.01	62018W.02
25w	4000k	3340	700	1,3	1/3	62012W.00	62012W.01	62012W.02
33w	4000k	4130	900	1,3	1/3	62016W.00	62016W.01	62016W.02
39w	4000k	4700	1050	1,3	1/3	62014W.00	62014W.01	62014W.02

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Opties:

- 1,5 meter snoer met 3-polige Shuko stekker
- 0,5 meter snoer + GST18i3 connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3 and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5 Blue connector male (dim)
- Andere RAL kleur
- 2700K, 3500k, 5000k of hogere CRI waarde 90/97
- Vlees, brood of Crisp White
- Micro prisma comfort afscherming (max. -3 UGR)
- IP65

Options:

- 1,5m cable with Shuko 3-pin plug
- 0,5 meter cable + GST18i3 connector (non - dimmable)
- 0,5 meter cable + GST18i3 and BST14i2 connector (dim)
- 0,5 meter cable + GST18i5 Blue connector male (dim)
- Different RAL color
- 2700k, 3500k, 5000k or higher CRI values 90/97
- Meat, bread or Crisp White
- Micro prism comfort diffuser (max. -3 UGR)
- IP65



62006W.00
12w 3000k 1715lm
ηLB 79%

