




Marici 195 Matt



Ronde LED downlight met een lage inbouwhoogte. Voorzien van decoratieve aluminium (99,9%) matte reflector (UGR<20). Gesatineerde PMMA afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (>79,0°) en hoge efficiency (max 136lm/w) met CRI>80. Wit gelakte (RAL 9003) aluminium behuizing. Wordt geleverd inclusief externe driver. Snelle en eenvoudige montage met veren. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with shallow build-in height. High gloss aluminium reflector (99,9%) with matt finish (UGR<20). Extra wide beam angle (>79,0°) and high efficiency (max 136lm/w) with CRI>80. Satinated PMMA diffuser for high comfort. White painted aluminium die cast body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including external driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <3. Fast and easy mounting with springs. Five years warranty.



Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali
9w	3000k	1170	250	1,3	1/3	62020W.00-M	62020W.01-M	62020W.02-M
12w	3000k	1585	350	1,3	1/3	62006W.00-M	62006W.01-M	62006W.02-M
18w	3000k	2185	500	1,3	1/3	62017W.00-M	62017W.01-M	62017W.02-M
25w	3000k	2935	700	1,3	1/3	62010W.00-M	62010W.01-M	62010W.02-M
33w	3000k	3635	900	1,3	1/3	62015W.00-M	62015W.01-M	62015W.02-M
39w	3000k	4125	1050	1,3	1/3	62013W.00-M	62013W.01-M	62013W.02-M
9w	4000k	1230	250	1,3	1/3	62021W.00-M	62021W.01-M	62021W.02-M
12w	4000k	1675	350	1,3	1/3	62007W.00-M	62007W.01-M	62007W.02-M
18w	4000k	2300	500	1,3	1/3	62018W.00-M	62018W.01-M	62018W.02-M
25w	4000k	3090	700	1,3	1/3	62012W.00-M	62012W.01-M	62012W.02-M
33w	4000k	3820	900	1,3	1/3	62016W.00-M	62016W.01-M	62016W.02-M
39w	4000k	4345	1050	1,3	1/3	62014W.00-M	62014W.01-M	62014W.02-M

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Opties:

- 1,5 meter snoer met 3-polige Shuko stekker
- 0,5 meter snoer + GST18i3 connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3 and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5 Blue connector male (dim)
- Andere RAL kleur
- 2700K, 3500k, 5000k of hogere CRI waarde 90/97
- Vlees, brood of Crisp White
- Micro prisma comfort afscherming (max. -3 UGR)
- IP65

Options:

- 1,5m cable with Shuko 3-pin plug
- 0,5 meter cable + GST18i3 connector (non - dimmable)
- 0,5 meter cable + GST18i3 and BST14i2 connector (dim)
- 0,5 meter cable + GST18i5 Blue connector male (dim)
- Different RAL color
- 2700k, 3500k, 5000k or higher CRI values 90/97
- Meat, bread or Crisp White
- Micro prism comfort diffuser (max. -3 UGR)
- IP65



62006W.00-M
12w 3000k 1585lm
ηLB 73%

