



62006W.00-W
12w 3000k 1610lm
ηLB 74%

Marici 195 White



Ronde LED downlight met een lage inbouwhoogte. Voorzien van decoratieve aluminium (99,9%) witte reflector (UGR<20). Gesatineerde PMMA afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (>79,0°) en hoge efficiency (max 138lm/w) met CRI>80. Wit gelakte (RAL 9003) aluminium behuizing. Wordt geleverd inclusief externe driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with shallow build-in height. High gloss aluminum reflector (99,9%) with white finish (UGR<20). Extra wide beam angle (>79,0°) and high efficiency (max 138lm/w) with CRI>80. Satinated PMMA diffuser for high comfort. White painted aluminum die cast body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including external driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <3. Fast and easy mounting with springs. Five years warranty.

| Wattage Watts | Kleur Colour | Lumen* Lumen* | Amperage (mA) Amperage (mA) | Gewicht (kg) Weight (kg) | Noodvoorz. (u) Emergency (h) | Artikel nr. Article no. | Dimbaar (1-10V) Dimmable (1-10V) | Dali |
|------------------|-----------------|------------------|--------------------------------|-----------------------------|---------------------------------|----------------------------|-------------------------------------|-------------|
| 9w | 3000k | 1185 | 250 | 1,3 | 1/3 | 62020W.00-W | 62020W.01-W | 62020W.02-W |
| 12w | 3000k | 1610 | 350 | 1,3 | 1/3 | 62006W.00-W | 62006W.01-W | 62006W.02-W |
| 18w | 3000k | 2215 | 500 | 1,3 | 1/3 | 62017W.00-W | 62017W.01-W | 62017W.02-W |
| 25w | 3000k | 2975 | 700 | 1,3 | 1/3 | 62010W.00-W | 62010W.01-W | 62010W.02-W |
| 33w | 3000k | 3680 | 900 | 1,3 | 1/3 | 62015W.00-W | 62015W.01-W | 62015W.02-W |
| 39w | 3000k | 4180 | 1050 | 1,3 | 1/3 | 62013W.00-W | 62013W.01-W | 62013W.02-W |
| 9w | 4000k | 1245 | 250 | 1,3 | 1/3 | 62021W.00-W | 62021W.01-W | 62021W.02-W |
| 12w | 4000k | 1700 | 350 | 1,3 | 1/3 | 62007W.00-W | 62007W.01-W | 62007W.02-W |
| 18w | 4000k | 2325 | 500 | 1,3 | 1/3 | 62018W.00-W | 62018W.01-W | 62018W.02-W |
| 25w | 4000k | 3130 | 700 | 1,3 | 1/3 | 62012W.00-W | 62012W.01-W | 62012W.02-W |
| 33w | 4000k | 3870 | 900 | 1,3 | 1/3 | 62016W.00-W | 62016W.01-W | 62016W.02-W |
| 39w | 4000k | 4400 | 1050 | 1,3 | 1/3 | 62014W.00-W | 62014W.01-W | 62014W.02-W |

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%

Opties:

- 1,5 meter snoer met 3-polige Shuko stekker
- 0,5 meter snoer + GST18i3 connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3 and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5 Blue connector male (dim)
- Andere RAL kleur
- 2700k, 3500k, 5000k of hogere CRI waarde 90/97
- Vlees, brood of Crisp White
- Micro prisma comfort afscherming (max. -3 UGR)
- IP65

Options:

- 1,5m cable with Shuko 3-pin plug
- 0,5 meter cable + GST18i3 connector (non - dimmable)
- 0,5 meter cable + GST18i3 and BST14i2 connector (dim)
- 0,5 meter cable + GST18i5 Blue connector male (dim)
- Different RAL color
- 2700k, 3500k, 5000k or higher CRI values 90/97
- Meat, bread or Crisp White
- Micro prism comfort diffuser (max. -3 UGR)
- IP65

