





Marici 195 White TW



Tunable white LED downlight met lage inbouwhoogte en dual satin PMMA afscherming. Brede bundel (>79°) en lage verblinding op maximaal vermogen (UGR<20). Wit gelakte aluminium reflector. Tunable white - dynamisch mengen van licht kleur tussen 2700K en 6500K (CRI>85). Wit gelakte (RAL 9003) aluminium behuizing. Zeer geschikt als basis verlichting in scholen, theaters en musea. Wordt geleverd inclusief externe DALI driver. Directe aansluiting op 220-240VAC. Kleurstabiliteit Mac Adam <3. Snelle en eenvoudige montage met veren. Onderhoudsvrij en hoge levensduurverwachting (50.000 uur L80B10). Vijf jaar garantie.



Tunable white modular LED downlight with dual satin PMMA diffuser. Wide beam angle (>79°) and low glare at maximum power (UGR<20). white painted aluminum reflector. Tunable white - dynamic mixing of light colour, linear colour mixing between 2700K and 6500K (CRI>85). White painted aluminum die cast body (RAL9003). Very suitable as general lighting in schools, theatres and museums. Delivered including external DALI driver. Direct connection to 220-240VAC. Colour stability, Mac Adam <3. Low maintenance and high life expectancy (50.000 hours L80B10). Fast and easy mounting with springs. Five years warranty.



Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.
16w	2700-6500k	1430	>85	1,3	1/3	62009W.16.TWW
22w	2700-6500k	2000	>85	1,3	1/3	62009W.22.TWW
31w	2700-6500k	2740	>85	1,3	1/3	62009W.31.TWW
40w	2700-6500k	3420	>85	1,3	1/3	62009W.40.TWW

* Lichtstroom van armatuur, tolerantie van +/- 10%


* Luminaire luminous flux, tolerance of +/- 10%

Opties:

- GST18i5 connector
- Andere RAL kleur
- Micro prisma comfort afscherming (max. -3 UGR)
- IP65

Options:

- GST18i5 connector
- Different RAL color
- Micro prism comfort diffuser (max. -3 UGR)
- IP65



62009W.31.TWW
31w 2700-6500K 2740lm
ηLB 74%

