





Pandora

Rond pendel LED armatuur met minimalistisch design. Behuizing gemaakt van gebogen aluminium profiel. Verkrijgbaar in wit gelakt (RAL 9003) zwart (RAL 9005) of zilver grijs (RAL 9006). Geschikt voor toepassing in onder andere winkelcentra, hotels en kantoren. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round pendant LED luminaire with minimalistic design. Housing made of aluminium profile painted in white (RAL 9003) black (RAL 9005) or silver grey (RAL 9006). Suitable for shopping centres, hotels and offices. Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <3. Warranty 5 years.



Micro Prisma / Micro Prism

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI	Diameter (mm) Length (mm)	Hoogte (mm) Height (mm)	Gewicht (kg) Weight (kg)	Artikel nr. Article no.	Dali
24w	3000k	2520	>80	400	82	-	26003MP_400.30	26003MP_400.32
41w	3000k	4300	>80	600	82	-	26003MP_600.30	26003MP_600.32
65w	3000k	6825	>80	900	82	-	26003MP_900.30	26003MP_900.32
85w	3000k	8925	>80	1200	82	-	26003MP_1200.30	26003MP_1200.32
140w	3000k	14.700	>80	2000	82	-	26003MP_2000.30	26003MP_2000.32
180w	3000k	18.900	>80	2500	82	-	26003MP_2500.30	26003MP_2500.32
220w	3000k	23.100	>80	3000	82	-	26003MP_3000.30	26003MP_3000.32
350w	3000k	36.750	>80	3500	82	-	26003MP_3500.30	26003MP_3500.32
24w	4000k	2650	>80	400	82	-	26003MP_400.40	26003MP_400.42
41w	4000k	4515	>80	600	82	-	26003MP_600.40	26003MP_600.42
65w	4000k	7170	>80	900	82	-	26003MP_900.40	26003MP_900.42
85w	4000k	9370	>80	1200	82	-	26003MP_1200.40	26003MP_1200.42
140w	4000k	15.435	>80	2000	82	-	26003MP_2000.40	26003MP_2000.42
180w	4000k	19.845	>80	2500	82	-	26003MP_2500.40	26003MP_2500.42
220w	4000k	24.255	>80	3000	82	-	26003MP_3000.40	26003MP_3000.42
350w	4000k	38.590	>80	3500	82	-	26003MP_3500.40	26003MP_3500.42

_ W=wit / B=zwart / G=grijs


_ W=white / B=black / G=grey

Opaal / Opal

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI	Diameter (mm) Length (mm)	Hoogte (mm) Height (mm)	Gewicht (kg) Weight (kg)	Artikel nr. Article no.	Dali
24w	3000k	2270	>80	400	82	-	26003OP_400.30	26003OP_400.32
41w	3000k	3870	>80	600	82	-	26003OP_600.30	26003OP_600.32
65w	3000k	6145	>80	900	82	-	26003OP_900.30	26003OP_900.32
85w	3000k	8035	>80	1200	82	-	26003OP_1200.30	26003OP_1200.32
140w	3000k	13.230	>80	2000	82	-	26003OP_2000.30	26003OP_2000.32
180w	3000k	17.000	>80	2500	82	-	26003OP_2500.30	26003OP_2500.32
220w	3000k	20.790	>80	3000	82	-	26003OP_3000.30	26003OP_3000.32
350w	3000k	33.075	>80	3500	82	-	26003MP_3500.30	26003MP_3500.32
24w	4000k	2385	>80	400	82	-	26003OP_400.40	26003OP_400.42
41w	4000k	4065	>80	600	82	-	26003OP_600.40	26003OP_600.42
65w	4000k	6455	>80	900	82	-	26003OP_900.40	26003OP_900.42
85w	4000k	8435	>80	1200	82	-	26003OP_1200.40	26003OP_1200.42
140w	4000k	13.895	>80	2000	82	-	26003OP_2000.40	26003OP_2000.42
180w	4000k	17.860	>80	2500	82	-	26003OP_2500.40	26003OP_2500.42
220w	4000k	21.830	>80	3000	82	-	26003OP_3000.40	26003OP_3000.42
350w	4000k	35.055	>80	3500	82	-	26003MP_3500.40	26003MP_3500.42

_ W=wit / B=zwart / G=grijs

_ W=white / B=black / G=grey



26003.MP_400.30
24w 3000k 2520 lumen
ηLB 100%

*Lichtstroom van armatuur, tolerantie van +/- 10%

*Luminaire luminous flux, tolerance of +/- 10%