


## Marici 240 Matt



Ronde LED downlight met een lage inbouwhoogte. Voorzien van decoratieve aluminium (99,9%) matte reflector (UGR<18). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (74,0°) en hoge efficiency (max 123lm/w) met CRI>80. Wit gelakte (RAL 9003) aluminium behuizing. Wordt geleverd inclusief externe driver. Snelle en eenvoudige montage met veren. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with shallow build-in height. High gloss aluminium reflector (99,9%) with matt finish (UGR<18). Extra wide beam angle (74,0°) and high efficiency (max 123lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted aluminium die cast body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including external driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting with springs. Five years warranty.



Wattage	Kleur	Lumen*	Amperage (mA)	kg	Noodvoorz. (u)	Artikel nr.	Dimbaar (1-10V)	Dali	Casambi
Watts	Colour	Lumen*	Amperage (mA)	kg	Emergency (h)	Article no.	Dimmable (1-10V)	Dali	Casambi
9w	3000k	1110	250	1,3	1/3	62022W.0930.M	62022W.0931.M	62022W.0932.M	62022W.0935.M
12w	3000k	1545	350	1,3	1/3	62022W.1230.M	62022W.1231.M	62022W.1232.M	62022W.1235.M
18w	3000k	2160	500	1,3	1/3	62022W.1830.M	62022W.1831.M	62022W.1832.M	62022W.1835.M
25w	3000k	2950	700	1,3	1/3	62022W.2530.M	62022W.2531.M	62022W.2532.M	62022W.2535.M
33w	3000k	3690	900	1,3	1/3	62022W.3330.M	62022W.3331.M	62022W.3332.M	62022W.3335.M
39w	3000k	4250	1050	1,3	1/3	62022W.3930.M	62022W.3931.M	62022W.3932.M	62022W.3935.M
9w	4000k	1170	250	1,3	1/3	62022W.0940.M	62022W.0941.M	62022W.0942.M	62022W.0945.M
12w	4000k	1625	350	1,3	1/3	62022W.1240.M	62022W.1241.M	62022W.1242.M	62022W.1245.M
18w	4000k	2270	500	1,3	1/3	62022W.1840.M	62022W.1841.M	62022W.1842.M	62022W.1845.M
25w	4000k	3100	700	1,3	1/3	62022W.2540.M	62022W.2541.M	62022W.2542.M	62022W.2545.M
33w	4000k	3875	900	1,3	1/3	62022W.3340.M	62022W.3341.M	62022W.3342.M	62022W.3345.M
39w	4000k	4385	1050	1,3	1/3	62022W.3940.M	62022W.3941.M	62022W.3942.M	62022W.3945.M

\* Lichtstroom van armatuur, tolerantie van +/- 10%

\* Luminaire luminous flux, tolerance of +/- 10%




### Opties:

- 1,5 meter snoer met 3-polige Shuko stekker
- 0,5 meter snoer + GST18i3 connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3 and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5 Blue connector male (dim)
- Andere RAL kleur
- 2700K, 3500k, 5000k of hogere CRI waarde 90/97
- Vlees, brood of Crisp White
- IP65

### Options:

- 1,5m cable with Shuko 3-pin plug
- 0,5 meter cable + GST18i3 connector (non - dimmable)
- 0,5 meter cable + GST18i3 and BST14i2 connector (dim)
- 0,5 meter cable + GST18i5 Blue connector male (dim)
- Different RAL color
- 2700k, 3500k, 5000k or higher CRI values 90/97
- Meat, bread or Crisp White
- IP65

Levensduurverwachting (uren)		
Life expectancy (hours)		
Watt	L80B10	L90B10
9	168.000	79.000
12	166.000	78.000
18	149.000	70.000
25	135.000	64.000
33	120.000	57.000
39	115.000	54.000



62022W.0930-M  
9w 3000k 1110lm  
ηLB 73%