




Marici 240 White



Ronde LED downlight met een lage inbouwhoogte. Voorzien van decoratieve aluminium (99,9%) witte reflector (UGR<18). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (73°) en hoge efficiency (max 125lm/w) met CRI>80. Wit gelakte (RAL 9003) aluminium behuizing. Wordt geleverd inclusief externe driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with shallow build-in height. High gloss aluminum reflector (99,9%) with white finish (UGR<18). Extra wide beam angle (73°) and high efficiency (max 125lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted aluminum die cast body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including external driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting with springs. Five years warranty.



| Wattage | Kleur | Lumen* | Amperage (mA) | kg | Noodvoorz. (u) | Artikel nr. | Dimbaar (1-10V) | Dali | Casambi |
|---------|--------|--------|---------------|-----|----------------|---------------|------------------|---------------|---------------|
| Watts | Colour | Lumen* | Amperage (mA) | kg | Emergency (h) | Article no. | Dimmable (1-10V) | Dali | Casambi |
| 9w | 3000k | 1125 | 250 | 1,3 | 1/3 | 62022W.0930.W | 62022W.0931.W | 62022W.0932.W | 62022W.0935.W |
| 12w | 3000k | 1565 | 350 | 1,3 | 1/3 | 62022W.1230.W | 62022W.1231.W | 62022W.1232.W | 62022W.1235.W |
| 18w | 3000k | 2190 | 500 | 1,3 | 1/3 | 62022W.1830.W | 62022W.1831.W | 62022W.1832.W | 62022W.1835.W |
| 25w | 3000k | 2990 | 700 | 1,3 | 1/3 | 62022W.2530.W | 62022W.2531.W | 62022W.2532.W | 62022W.2535.W |
| 33w | 3000k | 3745 | 900 | 1,3 | 1/3 | 62022W.3330.W | 62022W.3331.W | 62022W.3332.W | 62022W.3335.W |
| 39w | 3000k | 4310 | 1050 | 1,3 | 1/3 | 62022W.3930.W | 62022W.3931.W | 62022W.3932.W | 62022W.3935.W |
| 9w | 4000k | 1185 | 250 | 1,3 | 1/3 | 62022W.0940.W | 62022W.0941.W | 62022W.0942.W | 62022W.0945.W |
| 12w | 4000k | 1645 | 350 | 1,3 | 1/3 | 62022W.1240.W | 62022W.1241.W | 62022W.1242.W | 62022W.1245.W |
| 18w | 4000k | 2300 | 500 | 1,3 | 1/3 | 62022W.1840.W | 62022W.1841.W | 62022W.1842.W | 62022W.1845.W |
| 25w | 4000k | 3140 | 700 | 1,3 | 1/3 | 62022W.2540.W | 62022W.2541.W | 62022W.2542.W | 62022W.2545.W |
| 33w | 4000k | 3930 | 900 | 1,3 | 1/3 | 62022W.3340.W | 62022W.3341.W | 62022W.3342.W | 62022W.3345.W |
| 39w | 4000k | 4445 | 1050 | 1,3 | 1/3 | 62022W.3940.W | 62022W.3941.W | 62022W.3942.W | 62022W.3945.W |

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Opties:

- 1,5 meter snoer met 3-polige Shuko stekker
- 0,5 meter snoer + GST18i3 connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3 and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5 Blue connector male (dim)
- Andere RAL kleur
- 2700K, 3500k, 5000k of hogere CRI waarde 90/97
- Vlees, brood of Crisp White
- IP65

Options:

- 1,5m cable with Shuko 3-pin plug
- 0,5 meter cable + GST18i3 connector (non - dimmable)
- 0,5 meter cable + GST18i3 and BST14i2 connector (dim)
- 0,5 meter cable + GST18i5 Blue connector male (dim)
- Different RAL color
- 2700k, 3500k, 5000k or higher CRI values 90/97
- Meat, bread or Crisp White
- IP65

| Levensduurverwachting (uren) | | |
|------------------------------|---------|--------|
| Life expectancy (hours) | | |
| Watt | L80B10 | L90B10 |
| 9 | 168.000 | 79.000 |
| 12 | 166.000 | 78.000 |
| 18 | 149.000 | 70.000 |
| 25 | 135.000 | 64.000 |
| 33 | 120.000 | 57.000 |
| 39 | 115.000 | 54.000 |



62022W.1230.W
12w 3000k 1565lm
ηLB 74%