



23013W.31D.RGBM
31w 2330lm
ηLB 74%

Marici 150 Matt RGB-TW



RGB en Tunable white LED downlight met lage inbouwhoogte en gesatineerde PS Microprisma afscherming. Brede bundel (>77°) en lage verblinding op maximaal vermogen (UGR<21). Matte aluminium reflector. Voorzien van dimbaar RGB + tunable white LED technology (>100lm/w, 2500-7000k, CRI>90). Aanstuurbaar via DALI DT8 (slechts 1 BUS adres). RGB dimming 0-100%, CCT dimming 5-100%. Wit gelakte (RAL 9003) aluminium behuizing. Zeer geschikt als basis verlichting in scholen, theaters en musea. Inclusief DALI driver. Directe aansluiting op 48VDC of 220-240VAC. Zeer hoge initiële kleurstabiliteit Mac Adam <1. Snelle en eenvoudige montage met veren. Onderhoudsvrij en hoge levensduurverwachting (50.000 uur L90B10). Vijf jaar garantie.



RGB and tunable white modular LED downlight with low build-in height and satinated PS Microprism diffuser. Wide beam angle (>77°) and low glare at maximum power (UGR<21). Matt aluminum reflector. Build-in RGB + tunable white LED technology (>100lm/w, 2500-7000k, CRI>90). RGB dimming 0-100%, CCT dimming 5-100%. Controllable over DALI DT8 protocol (only 1 bus adress per luminaire). White painted die cast aluminum body (RAL9003). Ideal for schools, museums, theaters and hospitals. Delivered including DALI driver. Direct connection to 48VDC or 220-240VAC. Very high initial colour stability, Mac Adam <1. Low maintenance and high life expectancy (50.000 hours L90B10). Fast and easy mounting with springs. Five years warranty.

Wattage Watts	Lumen* Lumen*	CRI CRI	Gewicht (kg) Weight (kg)	48VDC 48VDC	220-240VAC 220-240VAC	Casambi Casambi
22w	1720	>90	0,9	23013W.22D.RGBM	23013W.22A.RGBM	23013W.22C.RGBM
31w	2330	>90	0,9	23013W.31D.RGBM	23013W.31A.RGBM	23013W.31C.RGBM

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%

Opties:

- GST18i3 connector + BST14i2 connector
- GST18i5 connector
- Andere RAL kleur
- IP65

Options:

- GST18i3 connector + BST14i2 connector
- GST18i5 connector
- Different RAL color
- IP65