




Marici 150 White RGB-TW



RGB en Tunable white LED downlight met lage inbouwhoogte en gesatineerde PS Microprisma afscherming. Brede bundel (>68°) en lage verblinding op maximaal vermogen (UGR<21). Wit gelakte aluminium reflector. Voorzien van dimbaar RGB + tunable white LED technology (>100lm/w, 2500-7000k, CRI>90). Aanstuurbaar via DALI DT8 (slechts 1 BUS adres). RGB dimming 0-100%, CCT dimming 5-100%. Wit gelakte (RAL 9003) aluminium behuizing. Zeer geschikt als basis verlichting in scholen, theaters en musea. Inclusief DALI driver Directe aansluiting op 48VDC of 220-240VAC. Zeer hoge initiële kleurstabiliteit Mac Adam <1. Snelle en eenvoudige montage met veren. Onderhoudsvrij en hoge levensduurverwachting (50.000 uur L90B10). Vijf jaar garantie.

RGB and tunable white modular LED downlight with low build-in height and a satinated PS Microprism diffuser. Wide beam angle (>68°) and low glare at maximum power (UGR<21). White painted aluminium reflector. Build-in RGB + tuneable white LED technology (>100lm/w, 2500-7000k, CRI>90). RGB dimming 0-100%, CCT dimming 5-100%. Controllable over DALI DT8 protocol (only 1 bus adress per luminaire). White painted die cast aluminum body (RAL9003). Ideal for schools, museums, theaters and hospitals. Delivered including DALI driver. Direct connection to 48VDC or 220-240VAC. Very high initial colour stability, Mac Adam <1. Low maintenance and high life expectancy (50.000 hours L90B10). Fast and easy mounting with springs. Five years warranty.



Wattage Watts	Lumen* Lumen*	CRI CRI	Gewicht (kg) Weight (kg)	48VDC 48VDC	220-240VDC 220-240VDC	Casambi Casambi
22w	1690	>90	0,9	23013W.22A.RGBW	23013W.22D.RGBW	23013W.22C.RGBW
31w	2180	>90	0,9	23013W.31A.RGBW	23013W.31D.RGBW	23013W.31C.RGBW

* Lichtstroom van armatuur, tolerantie van +/- 10%


* Luminaire luminous flux, tolerance of +/- 10%

Opties:

- GST18i3 connector + BST14i2 connector
- GST18i5 connector
- Andere RAL kleur
- IP65

Options:

- GST18i3 connector + BST14i2 connector
- GST18i5 connector
- Different RAL color
- IP65



23013W.31A.RGBW
31w 2180lm
ηLB 72%