Aeros Trim TW SUSPENDED

PF>0,95 IP40

Tunable White

Rond pendel LED armatuur gemaakt uit wit gelakt (RAL 9003) aluminium (optioneel zwart RAL 9005 of zilvergrijs RAL 9006). Homogeen verlichte diffuser van dual satin opaal PMMA of Microprisma. Gelijke licht dichtheid tussen verschillende afmetingen. Geschikt voor toepassing in onder andere winkelcentra, culturele gebouwen of kantoren. Tunable white - dynamisch mengen van licht kleur tussen 2700K en 6500K. Wordt geleverd inclusief pendel accessoires: staalkabels (3m) en snoer (3,5m). Onderhoudsarm en hoge levensduurverwachting (100.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round suspended LED luminaire made of white (RAL 9003) painted aluminium (optionally black RAL 9005 or silver grey RAL 9006). Completely homogeneously illuminated with dual satinised PMMA cover or micro prisma diffuser. Suitable for shopping centres, social and cultural amenities or representation areas. Tunable white - dynamic mixing of light colour, linear colour mixing between 2700K and 6500K. Delivered including pendant suspension, steel cables (3m) and mains cable (3,5m). Low maintenance and high life expectancy (100.000 hours L80B10). Colour stability, Mac Adam <3. Warranty five years.

Micro Prisma / *Micro Prism*

Wattage *Wattage*	**Kleur** *Colour*	**Lumen*** *Lumen**	**Diameter (mm)** *Diameter (mm)*	**kg** *kg*	**Noodvoorz. (u)** *Emergency (h)*	**Dali** *Dali*	**Casambi** *Casambi*
18w	2700-6500k	2340	350	3,2	1/3	26023_M.35.TW	26023_M.35.TWC
36w	2700-6500k	4680	600	4,4	1/3	26023_M.60.TW	26023_M.60.TWC
65w	2700-6500k	8450	900	6,5	1/3	26023_M.90.TW	26023_M.90.TWC
90w	2700-6500k	11.700	1200	9,0	1/3	26023_M.120.TW	26023_M.120.TWC

Opaal / *Opal*

Wattage *Wattage*	**Kleur** *Colour*	**Lumen*** *Lumen**	**Diameter (mm)** *Diameter (mm)*	**kg** *kg*	**Noodvoorz. (u)** *Emergency (h)*	**Dali** *Dali*	**Casambi** *Casambi*
18w	2700-6500k	2225	350	3,2	1/3	26023_OP.35.TW	26023_OP.35.TWC
36w	2700-6500k	4445	600	4,4	1/3	26023_OP.60.TW	26023_OP.60.TWC
65w	2700-6500k	8030	900	6,5	1/3	26023_OP.90.TW	26023_OP.90.TWC
90w	2700-6500k	11.115	1200	9,0	1/3	26023_OP.120.TW	26023_OP.120.TWC

* Lichtstroom van armatuur, tolerantie van +/- 10%

_ W=wit / B=zwart / G=grijs


* *Luminaire luminous flux, tolerance of +/- 10%*

_ W=white / B=black / G=grey



Opties:
- Geïntegreerde bewegingssensor
- EasySense-sensor

Options:
- *Integrated motionsensor*
- *EasySense-sensor*



26023_M.35.TW
18W 2700-6500K 2340lm
ηLB 100%

melis lighting