



Rond opbouw LED armatuur gemaakt uit wit gelakt (RAL 9003) aluminium (optioneel zwart RAL 9005 of zilvergrijs RAL 9006). Homogeen verlichte diffuser van dual satin opaal PMMA of Microprisma. Gelijke licht dichtheid tussen verschillende afmetingen. Geschikt voor toepassing in onder andere winkelcentra, culturele gebouwen of kantoren. Tunable white - dynamisch mengen van licht kleur tussen 2700K en 6500K. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round surface mounted luminaire made of white (RAL 9003) painted aluminium (optionally black RAL 9005 or silver grey RAL 9006). Completely homogeneously illuminated with dual satinised PMMA cover or micro prisma diffuser. Suitable for shopping centres, social and cultural amenities or representation areas. Tunable white - dynamic mixing of light colour, linear colour mixing between 2700K and 6500K. Low maintenance and high life expectancy (50.000 hours L90B10). Colour stability, Mac Adam <3. Warranty five years.

Micro Prisma / Micro Prism

Wattage Wattage	Kleur Colour	Lumen* Lumen*	Diameter (mm) Diameter (mm)	kg kg	Noodvoorz. (u) Emergency (h)	Dali Dali	Casambi Casambi
18w	2700-6500k	2270	350	3,2	1/3	26020_M.35.TW	26020_M.35.TWC
36w	2700-6500k	4535	600	4,4	1/3	26020_M.60.TW	26020_M.60.TWC
60w	2700-6500k	8190	900	6,5	1/3	26020_M.90.TW	26020_M.90.TWC
90w	2700-6500k	11.340	1200	9,0	1/3	26020_M.120.TW	26020_M.120.TWC

Opaal / Opal


Wattage Wattage	Kleur Colour	Lumen* Lumen*	Diameter (mm) Diameter (mm)	kg kg	Noodvoorz. (u) Emergency (h)	Dali Dali	Casambi Casambi
18w	2700-6500k	2160	350	3,2	1/3	26020_OP.35.TW	26020_OP.35.TWC
36w	2700-6500k	4320	600	4,4	1/3	26020_OP.60.TW	26020_OP.60.TWC
60w	2700-6500k	7800	900	6,5	1/3	26020_OP.90.TW	26020_OP.90.TWC
90w	2700-6500k	10.800	1200	9,0	1/3	26020_OP.120.TW	26020_OP.120.TWC

_ W=wit / B=zwart / G=grijs

_ W=white / B=black / G=grey

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Opties:

- Geïntegreerde bewegingssensor
- EasySense-sensor

Options:

- Integrated motionsensor
- EasySense-sensor



26020_M.35.TW

18W 2700-6500K 2270lm
ηLB 100%