



Rond opbouw LED armatuur gemaakt uit wit gelakt (RAL 9003) aluminium (optioneel zwart RAL 9005 of zilvergrijs RAL 9006). Homogeen verlichte diffuser van dual satin opaal PMMA of Microprisma. Gelijke licht dichtheid tussen verschillende afmetingen. Geschikt voor toepassing in onder andere winkelcentra, culturele gebouwen of kantoren. Tunable white - dynamisch mengen van licht kleur tussen 2700K en 6500K. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round surface mounted luminaire made of white (RAL 9003) painted aluminium (optionally black RAL 9005 or silver grey RAL 9006). Completely homogeneously illuminated with dual satinised PMMA cover or micro prisma diffuser. Suitable for shopping centres, social and cultural amenities or representation areas. Tunable white - dynamic mixing of light colour, linear colour mixing between 2700K and 6500K. Low maintenance and high life expectancy (50.000 hours L90B10). Colour stability, Mac Adam <3. Warranty five years.

Micro Prisma / Micro Prism

| Wattage<br>Wattage | Kleur<br>Colour | Lumen*<br>Lumen* | Diameter (mm)<br>Diameter (mm) | kg<br>kg | Noodvoorz. (u)<br>Emergency (h) | Dali<br>Dali   | Casambi<br>Casambi |
|--------------------|-----------------|------------------|--------------------------------|----------|---------------------------------|----------------|--------------------|
| 18w                | 2700-6500k      | 2340             | 350                            | 3,2      | 1/3                             | 26002_M.35.TW  | 26002_M.35.TWC     |
| 36w                | 2700-6500k      | 4680             | 600                            | 4,4      | 1/3                             | 26002_M.60.TW  | 26002_M.60.TWC     |
| 65w                | 2700-6500k      | 8450             | 900                            | 6,5      | 1/3                             | 26002_M.90.TW  | 26002_M.90.TWC     |
| 90w                | 2700-6500k      | 11.700           | 1200                           | 9,0      | 1/3                             | 26002_M.120.TW | 26002_M.120.TWC    |

Opaal / Opal


| Wattage<br>Wattage | Kleur<br>Colour | Lumen*<br>Lumen* | Diameter (mm)<br>Diameter (mm) | kg<br>kg | Noodvoorz. (u)<br>Emergency (h) | Dali<br>Dali    | Casambi<br>Casambi |
|--------------------|-----------------|------------------|--------------------------------|----------|---------------------------------|-----------------|--------------------|
| 18w                | 2700-6500k      | 2225             | 350                            | 3,2      | 1/3                             | 26002_OP.35.TW  | 26002_OP.35.TWC    |
| 36w                | 2700-6500k      | 4445             | 600                            | 4,4      | 1/3                             | 26002_OP.60.TW  | 26002_OP.60.TWC    |
| 65w                | 2700-6500k      | 8030             | 900                            | 6,5      | 1/3                             | 26002_OP.90.TW  | 26002_OP.90.TWC    |
| 90w                | 2700-6500k      | 11.115           | 1200                           | 9,0      | 1/3                             | 26002_OP.120.TW | 26002_OP.120.TWC   |

\_ W=wit / B=zwart / G=grijs

\_ W=white / B=black / G=grey

\* Lichtstroom van armatuur, tolerantie van +/- 10%

\* Luminaire luminous flux, tolerance of +/- 10%





OPBOUW ARMATUREN  
SURFACE MOUNTED LUMINAIRES



- Opties:**
- Geïntegreerde bewegingssensor
  - EasySense-sensor

- Options:**
- Integrated motionsensor
  - EasySense-sensor



**26002\_M.35.TW**  
18W 2700-6500K 2340lm  
ηLB 100%