


Ronde geminiaturiseerde LED downlight voor krachtige accentverlichting. Grote variëteit aan gefacetteerde hoog rendement hoogglans reflectoren met gehard helder glazen afscherming. Voorzien van subtiele gegoten aluminium afdekking (RAL 9003). Zeer geschikt voor hoge ruimtes of als aanlichting van producten in winkels. Wordt geleverd inclusief externe driver. Directe aansluiting op 220-240VAC. Snelle en eenvoudige montage met veren. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round miniaturised LED downlight for powerfull accent lighting. Large variety of faceted high efficiency reflectors with clear tempered glass diffuser. High efficiency aluminium reflector (>80%). Decorative die cast aluminium white painted (RAL 9003) trim. Very suitable for high rooms or as spot light in shops. Delivered including external driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (50.000 hours L90B10). Colour stability, Mac Adam <3. Fast and easy mounting with springs. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Graden Degree	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	1-10V 1-10V	Dali Dali
9w	3000k	1115	>80	10°	1,5	1/3	20039W.0910.30	20039W.0910.31	20039W.0910.32
13w	3000k	1470	>80	10°	1,5	1/3	20039W.1310.30	20039W.1310.31	20039W.1310.32
19w	3000k	1945	>80	10°	1,5	1/3	20039W.1910.30	20039W.1910.31	20039W.1910.32
28w	3000k	2430	>80	10°	1,5	1/3	20039W.2810.30	20039W.2810.31	20039W.2810.32
9w	3000k	1170	>80	15°	1,5	1/3	20039W.0915.30	20039W.0915.31	20039W.0915.32
12w	3000k	1585	>80	15°	1,5	1/3	20039W.1215.30	20039W.1215.31	20039W.1215.32
18w	3000k	2185	>80	15°	1,5	1/3	20039W.1815.30	20039W.1815.31	20039W.1815.32
25w	3000k	2935	>80	15°	1,5	1/3	20039W.2515.30	20039W.2515.31	20039W.2515.32
33w	3000k	3635	>80	15°	1,5	1/3	20039W.3315.30	20039W.3315.31	20039W.3315.32
39w	3000k	4125	>80	15°	1,5	1/3	20039W.3915.30	20039W.3915.31	20039W.3915.32
9w	3000k	1090	>80	30°	1,5	1/3	20039W.0930.30	20039W.0930.31	20039W.0930.32
12w	3000k	1475	>80	30°	1,5	1/3	20039W.1230.30	20039W.1230.31	20039W.1230.32
18w	3000k	2035	>80	30°	1,5	1/3	20039W.1830.30	20039W.1830.31	20039W.1830.32
25w	3000k	2735	>80	30°	1,5	1/3	20039W.2530.30	20039W.2530.31	20039W.2530.32
33w	3000k	3385	>80	30°	1,5	1/3	20039W.3330.30	20039W.3330.31	20039W.3330.32
39w	3000k	3845	>80	30°	1,5	1/3	20039W.3930.30	20039W.3930.31	20039W.3930.32
9w	3000k	995	>80	50°	1,5	1/3	20039W.0950.30	20039W.0950.31	20039W.0950.32
12w	3000k	1345	>80	50°	1,5	1/3	20039W.1250.30	20039W.1250.31	20039W.1250.32
18w	3000k	1855	>80	50°	1,5	1/3	20039W.1850.30	20039W.1850.31	20039W.1850.32
25w	3000k	2495	>80	50°	1,5	1/3	20039W.2550.30	20039W.2550.31	20039W.2550.32
33w	3000k	3085	>80	50°	1,5	1/3	20039W.3350.30	20039W.3350.31	20039W.3350.32
39w	3000k	3510	>80	50°	1,5	1/3	20039W.3950.30	20039W.3950.31	20039W.3950.32

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Opties:

- 1,5 meter snoer met 3-polige Schuko stekker
- 0,5 meter snoer + GST18i3 connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3 and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5 Blue connector male (dim)
- 2700K, 3500k, 5000k of hogere CRI waarde 90/97
- Vlees, brood of Crisp White

Options:

- 1,5m cable with Schuko 3-pin plug
- 0,5 meter cable + GST18i3 connector (non - dimmable)
- 0,5 meter cable + GST18i3 and BST14i2 connector (dim)
- 0,5 meter cable + GST18i5 Blue connector male (dim)
- 2700k, 3500k, 5000k or higher CRI values 90/97
- Meat, bread or Crisp White



20039W.1815.30

18w 3000k 15° 2185lm
ηLB 73%

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Graden Degree	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	1-10V 1-10V	Dali Dali
9w	4000k	1170	>80	10°	1,5	1/3	20039W.0910.40	20039W.0910.41	20039W.0910.42
13w	4000k	1540	>80	10°	1,5	1/3	20039W.1310.40	20039W.1310.41	20039W.1310.42
19w	4000k	2045	>80	10°	1,5	1/3	20039W.1910.40	20039W.1910.41	20039W.1910.42
28w	4000k	2550	>80	10°	1,5	1/3	20039W.2810.40	20039W.2810.41	20039W.2810.42
9w	4000k	1225	>80	15°	1,5	1/3	20039W.0915.40	20039W.0915.41	20039W.0915.42
12w	4000k	1670	>80	15°	1,5	1/3	20039W.1215.40	20039W.1215.41	20039W.1215.42
18w	4000k	2295	>80	15°	1,5	1/3	20039W.1815.40	20039W.1815.41	20039W.1815.42
25w	4000k	3090	>80	15°	1,5	1/3	20039W.2515.40	20039W.2515.41	20039W.2515.42
33w	4000k	3820	>80	15°	1,5	1/3	20039W.3315.40	20039W.3315.41	20039W.3315.42
39w	4000k	4345	>80	15°	1,5	1/3	20039W.3915.40	20039W.3915.41	20039W.3915.42
9w	4000k	1145	>80	30°	1,5	1/3	20039W.0930.40	20039W.0930.41	20039W.0930.42
12w	4000k	1560	>80	30°	1,5	1/3	20039W.1230.40	20039W.1230.41	20039W.1230.42
18w	4000k	2135	>80	30°	1,5	1/3	20039W.1830.40	20039W.1830.41	20039W.1830.42
25w	4000k	2875	>80	30°	1,5	1/3	20039W.2530.40	20039W.2530.41	20039W.2530.42
33w	4000k	3560	>80	30°	1,5	1/3	20039W.3330.40	20039W.3330.41	20039W.3330.42
39w	4000k	4045	>80	30°	1,5	1/3	20039W.3930.40	20039W.3930.41	20039W.3930.42
9w	4000k	1045	>80	50°	1,5	1/3	20039W.0950.40	20039W.0950.41	20039W.0950.42
12w	4000k	1420	>80	50°	1,5	1/3	20039W.1250.40	20039W.1250.41	20039W.1250.42
18w	4000k	1945	>80	50°	1,5	1/3	20039W.1850.40	20039W.1850.41	20039W.1850.42
25w	4000k	2625	>80	50°	1,5	1/3	20039W.2550.40	20039W.2550.41	20039W.2550.42
33w	4000k	3245	>80	50°	1,5	1/3	20039W.3350.40	20039W.3350.41	20039W.3350.42
39w	4000k	3690	>80	50°	1,5	1/3	20039W.3950.40	20039W.3950.41	20039W.3950.42

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%

