


Ronde waterdichte (IP65) LED downlight voor krachtige basisverlichting. Hoog rendement gefacetteerde hoogglans reflector (LOR>80%), 35° bundel, met helder gehard glazen afscherming. Voorzien van gegoten aluminium afdekking in outdoor kwaliteit RAL 9003 poederlak. Zeer goed toepasbaar in overkappingen met veel waterinslag of buitengebieden nabij water. Wordt geleverd inclusief interne driver. Directe aansluiting op 220-240VAC. Snelle en eenvoudige montage met veren. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round waterproof (IP65) LED downlight for powerful general lighting. Faceted high efficiency reflector (LOR>80%) with clear tempered glass diffuser with 35 degree beam angle. Die cast aluminium outdoor quality white powder coated (RAL 9003) trim. Very suitable in roof covers or near water areas with lots of spray water. Delivered including internal driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (50.000 hours L90B10). Colour stability, Mac Adam <3. Fast and easy mounting with springs. Five year warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI (Ra) CRI (Ra)	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	1-10V 1-10V	Dali Dali
12w	3000k	1590	>80	2	1/3	60623W.12.30	60623W.12.31	60623W.12.32
12w	4000k	1630	>80	2	1/3	60623W.12.40	60623W.12.41	60623W.12.42
17w	3000k	2160	>80	2	1/3	60623W.17.30	60623W.17.31	60623W.17.32
17w	4000k	2220	>80	2	1/3	60623W.17.40	60623W.17.41	60623W.17.42
25w	3000k	2870	>80	2	1/3	60623W.25.30	60623W.25.31	60623W.25.32
25w	4000k	2975	>80	2	1/3	60623W.25.40	60623W.25.41	60623W.25.42

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Opties:

- 1,5 meter snoer met 3-polige Shuko stekker
- 0,5 meter snoer + GST18i3® connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3® and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5® Blue connector male (dim)
- Andere RAL kleur
- 2700K, 3500k, 5000k of hogere CRI waarde 90/97

Options:

- 1,5m cable with Shuko 3-pin plug
- 0,5 meter cable + GST18i3® connector (non - dimmable)
- 0,5 meter cable + GST18i3® and BST14i2 connector (dim)
- 0,5 meter cable + GST18i5® Blue connector male (dim)
- Different RAL color
- 2700k, 3500k, 5000k or higher CRI values 90/97



60623W.25.30

25w 3000k 2870lm
ηLB 81,4%