

Argon Micro TW




Decoratief Tunable White inlegarmatuur met standaard afmetingen voor systeemplafonds (M600) of gipsplafonds met hoog armatuur rendement (>125lm/w). Aanstuurbaar via Dali DT8 of Casambi. Vervaardigd uit witgelakt (RAL 9003) plaatstaal. Directe verlichting via opaal en micro prisma afscherming. Brede uitstralingshoek (>100°) en zeer lage verblinding (UGR<19). Hierdoor zeer goed toepasbaar in gangen, kantoren, klaslokalen, en andere werkruimtes waar hoge eisen aan comfort worden gesteld. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L70). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Decorative recessed luminaire with standard measurements for suspended ceilings (M600) or plasterboard ceilings with high luminaire efficiency (>125lm/w). Controllable trough Dali DT8 or Casambi. Housing made of white painted (RAL 9003) sheet metal. Direct lighting through opal and micro prisma diffuser. Low glare (UGR <19) and wide beam angle >100°. Very suitable in corridors, offices, classrooms and other working areas where there are high demands for comfortable light. Low maintenance and high life expectancy (50.000 hours L70). Colour stability, Mac Adam <3. Warranty 5 years.

Wattage Watts	Kleur Colour	Lumen Lumen	CRI (Ra) CRI (Ra)	Breedte (mm) Width (mm)	Lengte (mm) Length (mm)	Hoogte (mm) Height (mm)	kg kg	Noodvoorz. (u) Emergency (h)	Dali Dali	Casambi Casambi
25w	2700-6500k	3125	>80	595	595	65	6	1/3	29516MA.25.TW	29516MA.25.TWC
32w	2700-6500k	4000	>80	595	595	65	6	1/3	29516MA.32.TW	29516MA.32.TWC
38w	2700-6500k	4750	>80	595	595	65	6	1/3	29516MA.38.TW	29516MA.38.TWC
52w	2700-6500k	6500	>80	595	595	65	6	1/3	29516MA.52.TW	29516MA.52.TWC
38w	2700-6500k	4750	>80	295	1195	65	6	1/3	29516MB.38.TW	29516MB.38.TWC
76w	2700-6500k	9500	>80	295	1195	65	6	1/3	29516MB.76.TW	29516MB.76.TWC

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



INBOUW ARMATUREN RECESSED LUMINAIRES




Opties:

- Daglichtregeling
- Bewegingsmelder
- Daglichtregeling & bewegingssensor
- GST18i3® connector + BST14i2 connector
- GST18i5® connector
- Andere RAL kleur

Optional:

- Daylight control sensor
- Motion sensor
- Daylight control & motion sensor
- GST18i3® connector + BST14i2 connector
- GST18i5® connector
- Different RAL colour



29516MA.25.TW
25w 2700-6500k 3125lm
ηLB 100%