Argon Micro

PF>0,95 IP20-54


Decoratief inlegarmatuur met standaard afmetingen voor systeemplafonds (M600) of gipsplafonds met hoog armatuur rendement (>125lm/w). Vervaardigd uit witgelakt (RAL 9003) plaatstaal. Directe verlichting via opaal en micro prisma afscherming. Brede uitstralingshoek (>100º) en zeer lage verblinding (UGR<19).Hierdoor zeer goed toepasbaar in gangen, kantoren, klaslokalen, en andere werkruimtes waar hoge eisen aan comfort worden gesteld. Onderhoudsarm en hoge levensduurverwachting (100.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Decorative recessed luminaire with standard measurements for suspended ceilings (M600) or plasterboard ceilings with high luminaire efficiency (>125lm/w). Housing made of white painted (RAL 9003) sheet metal. Direct lighting through opal and micro prisma diffusor. Low glare (UGR <19) and wide beam angle >100º. Very suitable in corridors, offices, classrooms and other working areas where there are high demands for comfortable light. Low maintenance and high life expectancy (100.000 hours L80B10). Colour stability, Mac Adam <3. Warranty 5 years.

Wattage *Watts*	**Kleur** *Colour*	**Lumen** *Lumen*	**CRI (Ra)** *CRI (Ra)*	**Breedte (mm)** *Width (mm)*	**Lengte (mm)** *Length (mm)*	**Hoogte (mm)** *Height (mm)*	**Gewicht (kg)** *Weight (kg)*	**Noodvoorz. (u)** *Emergency (h)*	**Artikel nr.** *Article no.*	**Dali** *Dali*	**EasySense** *EasySense*
16w	3000k	1900	>80	295	595	65	3	1/3	29516MA.16.30	29516MA.16.32	29516MA.16.37
26w	3000k	3085	>80	295	595	65	3	1/3	29516MA.26.30	29516MA.26.32	29516MA.26.37
25w	3000k	2970	>80	595	595	65	6	1/3	29516MA.25.30	29516MA.25.32	29516MA.25.37
32w	3000k	3800	>80	595	595	65	6	1/3	29516MA.32.30	29516MA.32.32	29516MA.32.37
38w	3000k	4510	>80	595	595	65	6	1/3	29516MA.38.30	29516MA.38.32	29516MA.38.37
52w	3000k	6175	>80	595	595	65	6	1/3	29516MA.52.30	29516MA.52.32	29516MA.52.37
38w	3000k	4510	>80	295	1195	65	6	1/3	29516MB.38.30	29516MB.38.32	29516MB.38.37
76w	3000k	9025	>80	295	1195	65	6	1/3	29516MB.76.30	29516MB.76.32	29516MB.76.37
16w	4000k	2000	>80	295	595	65	6	1/3	29516MA.16.40	29516MA.16.42	29516MA.16.47
26w	4000k	3250	>80	295	595	65	6	1/3	29516MA.26.40	29516MA.26.42	29516MA.26.47
25w	4000k	3125	>80	595	595	65	6	1/3	29516MA.25.40	29516MA.25.42	29516MA.25.47
32w	4000k	4000	>80	595	595	65	6	1/3	29516MA.32.40	29516MA.32.42	29516MA.32.47
38w	4000k	4750	>80	595	595	65	6	1/3	29516MA.38.40	29516MA.38.42	29516MA.38.47
52w	4000k	6500	>80	595	595	65	6	1/3	29516MA.52.40	29516MA.52.42	29516MA.52.47
38w	4000k	4750	>80	295	1195	65	6	1/3	29516MB.38.40	29516MB.38.42	29516MB.38.47
76w	4000k	9500	>80	295	1195	65	6	1/3	29516MB.76.40	29516MB.76.42	29516MB.76.47

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*








Opties:
- Daglichtregeling
- Bewegingsmelder
- Daglichtregeling & bewegingssensor
- GST18i3® connector + BST14i2 connector
- GST18i5® connector
- Andere RAL kleur

Optional:
- *Daylight control sensor*
- *Motion sensor*
- *Daylight control & motion sensor*
- *GST18i3® connector + BST14i2 connector*
- *GST18i5® connector*
- *Different RAL colour*



29516MA.16.30
16w 3000k 1900lm
ηLB 100%

melis lighting