

Aron Tilt 152 Honey WHITE




Ronde kantelbare LED downlight voor krachtige accentverlichting. 350° draaibaar en 25° kantelbaar. Gefacetteerde hoogglans 99,98% aluminium reflector met honingraat afscherming voor extra comfort (UGR<15). Dankzij een modulaire ring kunnen verschillende accessoires op de Aron geklikt worden. Hierdoor zeer geschikt als accent verlichting in hotels en winkels. Verkrijgbaar in wit (RAL 9003) en zwart (RAL 9005). Wordt geleverd inclusief externe driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B10). Kleur stabiliteit, Mac Adam <3. Snelle en eenvoudige montage met veren. Vijf jaar garantie.

Round tiltable LED downlight for powerful accent lighting. Rotates through 350° and pivots through 25°. Faceted glossy 99,98% aluminium reflector with honeycomb shielding for extra comfort (UGR<15). Onto the modular die cast aluminium trim several accessories can be clicked making it very suitable as spot light in shops, hotels and restaurants. Standard available in RAL 9003 (white) or RAL 9005 (black). Delivered including external driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (50.000 hours L90B10). Colour stability, Mac Adam <3. Fast and easy mounting with springs. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Graden Degree	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikel nr.* Article no.*	1-10V 1-10V	Dali Dali
9w	3000k	815	>80	20°	1,6	1/3	20042HW.0920.30	20042HW.0920.31	20042HW.0920.32
12w	3000k	1110	>80	20°	1,6	1/3	20042HW.1220.30	20042HW.1220.31	20042HW.1220.32
18w	3000k	1525	>80	20°	1,6	1/3	20042HW.1820.30	20042HW.1820.31	20042HW.1820.32
25w	3000k	2050	>80	20°	1,6	1/3	20042HW.2520.30	20042HW.2520.31	20042HW.2520.32
33w	3000k	2540	>80	20°	1,6	1/3	20042HW.3320.30	20042HW.3320.31	20042HW.3320.32
39w	3000k	2880	>80	20°	1,6	1/3	20042HW.3920.30	20042HW.3920.31	20042HW.3920.32
9w	3000k	815	>80	40°	1,6	1/3	20042HW.0940.30	20042HW.0940.31	20042HW.0940.32
12w	3000k	1110	>80	40°	1,6	1/3	20042HW.1240.30	20042HW.1240.31	20042HW.1240.32
18w	3000k	1525	>80	40°	1,6	1/3	20042HW.1840.30	20042HW.1840.31	20042HW.1840.32
25w	3000k	2050	>80	40°	1,6	1/3	20042HW.2540.30	20042HW.2540.31	20042HW.2540.32
33w	3000k	2540	>80	40°	1,6	1/3	20042HW.3340.30	20042HW.3340.31	20042HW.3340.32
39w	3000k	2880	>80	40°	1,6	1/3	20042HW.3940.30	20042HW.3940.31	20042HW.3940.32
9w	4000k	860	>80	20°	1,6	1/3	20042HW.0920.40	20042HW.0920.41	20042HW.0920.42
12w	4000k	1170	>80	20°	1,6	1/3	20042HW.1220.40	20042HW.1220.41	20042HW.1220.42
18w	4000k	1600	>80	20°	1,6	1/3	20042HW.1820.40	20042HW.1820.41	20042HW.1820.42
25w	4000k	2160	>80	20°	1,6	1/3	20042HW.2520.40	20042HW.2520.41	20042HW.2520.42
33w	4000k	2670	>80	20°	1,6	1/3	20042HW.3320.40	20042HW.3320.41	20042HW.3320.42
39w	4000k	3035	>80	20°	1,6	1/3	20042HW.3920.40	20042HW.3920.41	20042HW.3920.42
9w	4000k	860	>80	40°	1,6	1/3	20042HW.0940.40	20042HW.0940.41	20042HW.0940.42
12w	4000k	1170	>80	40°	1,6	1/3	20042HW.1240.40	20042HW.1240.41	20042HW.1240.42
18w	4000k	1600	>80	40°	1,6	1/3	20042HW.1840.40	20042HW.1840.41	20042HW.1840.42
25w	4000k	2160	>80	40°	1,6	1/3	20042HW.2540.40	20042HW.2540.41	20042HW.2540.42
33w	4000k	2670	>80	40°	1,6	1/3	20042HW.3340.40	20042HW.3340.41	20042HW.3340.42
39w	4000k	3035	>80	40°	1,6	1/3	20042HW.3940.40	20042HW.3940.41	20042HW.3940.42

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



SPOTS SPOTS




Opties:

- 1,5 meter snoer met 3-polige Schuko stekker
- 0,5 meter snoer + GST18i3® connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3® and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5® Blue connector male (dim)
- 2700K, 3500k, 5000k of hogere CRI waarde 90/97
- Vlees, brood of Crisp White

Options:

- 1,5m cable with Schuko 3-pin plug
- 0,5 meter cable + GST18i3® connector (non - dimmable)
- 0,5 meter cable + GST18i3® and BST14i2 connector (dim)
- 0,5 meter cable + GST18i5® Blue connector male (dim)
- 2700k, 3500k, 5000k or higher CRI values 90/97
- Meat, bread or Crisp White



20042HW.2540.30
25w 3000k 40° 2050lm
ηLB 51%

melis lighting