


Decoratief opbouw armatuur met afgeronde hoeken en hoog rendement LED technologie (>135lm/w). Vervaardigd uit witgelakt (RAL 9003) plaatstaal. Hoogglans aluminium Miro reflector met lage verblinding (UGR<17) en brede uitstralingshoek >90°. Hierdoor zeer goed toepasbaar in kantoren, klaslokalen, en andere werkkruimtes waar hoge eisen aan comfort worden gesteld. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B50). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Decorative surface mounted luminaire with bevelled edges and high efficiency LED technology (>135lm/w). Housing made of white painted (RAL 9003) sheet metal. With specular aluminum Miro louvre with low glare (UGR<17) and wide beam angle >90°. Therefore very suitable for offices, classrooms and other working areas where there are high demands for comfortable light. Low maintenance and high life expectancy (50.000 hours L90B50). Colour stability, Mac Adam <3. Warranty 5 years.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI (Ra) CRI (Ra)	B (mm) W (mm)	L (mm) L (mm)	H (mm) H (mm)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dali Dali	EasySense EasySense
15W	3000k	1970	>80	250	626	60	2,5	1/3	29524W.A15.30	29524W.A15.32	29524W.A15.37
28W	3000k	3480	>80	348	626	60	4	1/3	29524W.A28.30	29524W.A28.32	29524W.A28.37
38W	3000k	4540	>80	348	626	60	4	1/3	29524W.A38.30	29524W.A38.32	29524W.A38.37
57W	3000k	6480	>80	348	626	60	4	1/3	29524W.A57.30	29524W.A57.32	29524W.A57.37
28W	3000k	3540	>80	445	626	60	4	1/3	29524W.B28.30	29524W.B28.32	29524W.B28.37
38W	3000k	4710	>80	445	626	60	4	1/3	29524W.B38.30	29524W.B38.32	29524W.B38.37
57W	3000k	6755	>80	445	626	60	4	1/3	29524W.B57.30	29524W.B57.32	29524W.B57.37
15W	3000k	1970	>80	150	1186	60	3	1/3	29524W.C15.30	29524W.C15.32	29524W.C15.37
29W	3000k	3460	>80	150	1186	60	3	1/3	29524W.C29.30	29524W.C29.32	29524W.C29.37
28W	3000k	3540	>80	250	1186	60	4	1/3	29524W.C28.30	29524W.C28.32	29524W.C28.37
38W	3000k	4710	>80	250	1186	60	4	1/3	29524W.C38.30	29524W.C38.32	29524W.C38.37
57W	3000k	6755	>80	250	1186	60	4	1/3	29524W.C57.30	29524W.C57.32	29524W.C57.37
58W	3000k	7000	>80	348	1186	60	7	1/3	29524W.C58.30	29524W.C58.32	29524W.C58.37
78W	3000k	9170	>80	348	1186	60	7	1/3	29524W.C78.30	29524W.C78.32	29524W.C78.37
98W	3000k	11.275	>80	348	1186	60	7	1/3	29524W.C98.30	29524W.C98.32	29524W.C98.37
18W	3000k	2250	>80	150	1466	60	4	1/3	29524W.D18.30	29524W.D18.32	29524W.D18.37
27W	3000k	3325	>80	150	1466	60	4	1/3	29524W.D27.30	29524W.D27.32	29524W.D27.37
50W	3000k	5715	>80	150	1466	60	4	1/3	29524W.D50.30	29524W.D50.32	29524W.D50.37
37W	3000k	4650	>80	250	1466	60	9	1/3	29524W.D37.30	29524W.D37.32	29524W.D37.37
55W	3000k	6690	>80	250	1466	60	9	1/3	29524W.D55.30	29524W.D55.32	29524W.D55.37
75W	3000k	8720	>80	250	1466	60	9	1/3	29524W.D75.30	29524W.D75.32	29524W.D75.37

\* Lichtstroom van armatuur, tolerantie van +/- 10%

\* Luminaire luminous flux, tolerance of +/- 10%




#### Opties:

- Daglicht en bewegingsregeling ingebouwd in de diffuser
- EasySense Sensor
- 6500k
- CRI > 90

#### Options:

- Daylight and motion control sensor build into the diffuser
- EasySense Sensor
- 6500k
- CRI > 90



**29524W.A28.30**  
28w 3000k 3480lm  
ηLB 100%

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI (Ra) CRI (Ra)	B (mm) W (mm)	L (mm) L (mm)	H (mm) H (mm)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dali Dali	EasySense EasySense
15W	4000k	2070	>80	250	626	60	2,5	1/3	29524W.A15.40	29524W.A15.42	29524W.A15.47
28W	4000k	3665	>80	348	626	60	4	1/3	29524W.A28.40	29524W.A28.42	29524W.A28.47
38W	4000k	4780	>80	348	626	60	4	1/3	29524W.A38.40	29524W.A38.42	29524W.A38.47
57W	4000k	6820	>80	348	626	60	4	1/3	29524W.A57.40	29524W.A57.42	29524W.A57.47
28W	4000k	3725	>80	445	626	60	4	1/3	29524W.B28.40	29524W.B28.42	29524W.B28.47
38W	4000k	4955	>80	445	626	60	4	1/3	29524W.B38.40	29524W.B38.42	29524W.B38.47
57W	4000k	7110	>80	445	626	60	4	1/3	29524W.B57.40	29524W.B57.42	29524W.B57.47
15W	4000k	2070	>80	150	1186	60	3	1/3	29524W.C15.40	29524W.C15.42	29524W.C15.47
29W	4000k	3640	>80	150	1186	60	3	1/3	29524W.C29.40	29524W.C29.42	29524W.C29.47
28W	4000k	3725	>80	250	1186	60	4	1/3	29524W.C28.40	29524W.C28.42	29524W.C28.47
38W	4000k	4955	>80	250	1186	60	4	1/3	29524W.C38.40	29524W.C38.42	29524W.C38.47
57W	4000k	7110	>80	250	1186	60	4	1/3	29524W.C57.40	29524W.C57.42	29524W.C57.47
58W	4000k	7365	>80	348	1186	60	7	1/3	29524W.C58.40	29524W.C58.42	29524W.C58.47
78W	4000k	9650	>80	348	1186	60	7	1/3	29524W.C78.40	29524W.C78.42	29524W.C78.47
98W	4000k	11.870	>80	348	1186	60	7	1/3	29524W.C98.40	29524W.C98.42	29524W.C98.47
18W	4000k	2375	>80	150	1466	60	4	1/3	29524W.D18.40	29524W.D18.42	29524W.D18.47
27W	4000k	3500	>80	150	1466	60	4	1/3	29524W.D27.40	29524W.D27.42	29524W.D27.47
50W	4000k	6015	>80	150	1466	60	4	1/3	29524W.D50.40	29524W.D50.42	29524W.D50.47
37W	4000k	4895	>80	250	1466	60	9	1/3	29524W.D37.40	29524W.D37.42	29524W.D37.47
55W	4000k	7040	>80	250	1466	60	9	1/3	29524W.D55.40	29524W.D55.42	29524W.D55.47
75W	4000k	9180	>80	250	1466	60	9	1/3	29524W.D75.40	29524W.D75.42	29524W.D75.47

\* Lichtstroom van armatuur, tolerantie van +/- 10%

\* Luminaire luminous flux, tolerance of +/- 10%

