


Opbouw armatuur met hoog rendement LED technologie (>125lm/w). Vervaardigd uit witgelakt (RAL 9003) plaatstaal. Hoogglans aluminium Miro reflector met lage verblinding (UGR<17) en brede uitstralingshoek >90°. Hierdoor zeer goed toepasbaar in kantoren, klaslokalen, en andere werkkruimtes waar hoge eisen aan comfort worden gesteld. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B50). Kleur stabiliteit, Mac Adam <3. Riscoklasse RG0. Vijf jaar garantie.

Surface mounted luminaire with high efficiency LED technology (>125lm/w). Housing made of white painted (RAL 9003) sheet metal. With specular aluminum Miro louvre with low glare (UGR<17) and wide beam angle >90°. Therefore very suitable for offices, classrooms and other working areas where there are high demands for comfortable light. Low maintenance and high life expectancy (50.000 hours L90B50). Colour stability, Mac Adam <3. Risk class RG0 Warranty 5 years.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI (Ra) CRI (Ra)	B (mm) W (mm)	L (mm) L (mm)	H (mm) H (mm)	kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dali Dali	EasySense EasySense
15W	3000k	1810	>80	230	605	42	2,5	1/3	29523W.A15.30	29523W.A15.32	29523W.A15.37
28W	3000k	3315	>80	327	605	42	4	1/3	29523W.A28.30	29523W.A28.32	29523W.A28.37
38W	3000k	4405	>80	327	605	42	4	1/3	29523W.A38.30	29523W.A38.32	29523W.A38.37
57W	3000k	6445	>80	327	605	42	4	1/3	29523W.A57.30	29523W.A57.32	29523W.A57.37
28W	3000k	3380	>80	425	605	42	4	1/3	29523W.B28.30	29523W.B28.32	29523W.B28.37
38W	3000k	4480	>80	425	605	42	4	1/3	29523W.B38.30	29523W.B38.32	29523W.B38.37
57W	3000k	6550	>80	425	605	42	4	1/3	29523W.B57.30	29523W.B57.32	29523W.B57.37
15W	3000k	1810	>80	130	1165	42	3	1/3	29523W.C15.30	29523W.C15.32	29523W.C15.37
29W	3000k	3415	>80	130	1165	42	3	1/3	29523W.C29.30	29523W.C29.32	29523W.C29.37
28W	3000k	3380	>80	230	1165	42	4	1/3	29523W.C28.30	29523W.C28.32	29523W.C28.37
38W	3000k	4490	>80	230	1165	42	4	1/3	29523W.C38.30	29523W.C38.32	29523W.C38.37
57W	3000k	6555	>80	230	1165	42	4	1/3	29523W.C57.30	29523W.C57.32	29523W.C57.37
58W	3000k	7000	>80	327	1165	42	7	1/3	29523W.C58.30	29523W.C58.32	29523W.C58.37
78W	3000k	9190	>80	327	1165	42	7	1/3	29523W.C78.30	29523W.C78.32	29523W.C78.37
98W	3000k	11.265	>80	327	1165	42	7	1/3	29523W.C98.30	29523W.C98.32	29523W.C98.37
18W	3000k	2175	>80	130	1445	42	4	1/3	29523W.D18.30	29523W.D18.32	29523W.D18.37
27W	3000k	3180	>80	130	1445	42	4	1/3	29523W.D27.30	29523W.D27.32	29523W.D27.37
50W	3000k	5750	>80	130	1445	42	4	1/3	29523W.D50.30	29523W.D50.32	29523W.D50.37
37W	3000k	4465	>80	230	1445	42	9	1/3	29523W.D37.30	29523W.D37.32	29523W.D37.37
55W	3000k	6480	>80	230	1445	42	9	1/3	29523W.D55.30	29523W.D55.32	29523W.D55.37
75W	3000k	8620	>80	230	1445	42	9	1/3	29523W.D75.30	29523W.D75.32	29523W.D75.37

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



OPBOUW ARMATUREN SURFACE MOUNTED LUMINAIRES




Opties:

- Daglicht en bewegingsregeling ingebouwd in de diffuser
- EasySense Sensor
- 6500k
- CRI > 90

Options:

- Daylight and motion control sensor build into the diffuser
- EasySense Sensor
- 6500k
- CRI > 90



29523W.A15.30

15w 3000k 1810lm
ηLB 100%

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI (Ra) CRI (Ra)	B (mm) W (mm)	L (mm) L (mm)	H (mm) H (mm)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dali Dali	EasySense EasySense
15W	4000k	1905	>80	230	605	42	2,5	1/3	29523W.A15.40	29523W.A15.42	29523W.A15.47
28W	4000k	3490	>80	327	605	42	4	1/3	29523W.A28.40	29523W.A28.42	29523W.A28.47
38W	4000k	4636	>80	327	605	42	4	1/3	29523W.A38.40	29523W.A38.42	29523W.A38.47
57W	4000k	6783	>80	327	605	42	4	1/3	29523W.A57.40	29523W.A57.42	29523W.A57.47
28W	4000k	3556	>80	425	605	42	4	1/3	29523W.B28.40	29523W.B28.42	29523W.B28.47
38W	4000k	4712	>80	425	605	42	4	1/3	29523W.B38.40	29523W.B38.42	29523W.B38.47
57W	4000k	6897	>80	425	605	42	4	1/3	29523W.B57.40	29523W.B57.42	29523W.B57.47
15W	4000k	1905	>80	130	1165	42	3	1/3	29523W.C15.40	29523W.C15.42	29523W.C15.47
29W	4000k	3596	>80	130	1165	42	3	1/3	29523W.C29.40	29523W.C29.42	29523W.C29.47
28W	4000k	3556	>80	230	1165	42	4	1/3	29523W.C28.40	29523W.C28.42	29523W.C28.47
38W	4000k	4723	>80	230	1165	42	4	1/3	29523W.C38.40	29523W.C38.42	29523W.C38.47
57W	4000k	6897	>80	230	1165	42	4	1/3	29523W.C57.40	29523W.C57.42	29523W.C57.47
58W	4000k	7366	>80	327	1165	42	7	1/3	29523W.C58.40	29523W.C58.42	29523W.C58.47
78W	4000k	9672	>80	327	1165	42	7	1/3	29523W.C78.40	29523W.C78.42	29523W.C78.47
98W	4000k	11.858	>80	327	1165	42	7	1/3	29523W.C98.40	29523W.C98.42	29523W.C98.47
18W	4000k	2286	>80	130	1445	42	4	1/3	29523W.D18.40	29523W.D18.42	29523W.D18.47
27W	4000k	3348	>80	130	1445	42	4	1/3	29523W.D27.40	29523W.D27.42	29523W.D27.47
50W	4000k	6050	>80	130	1445	42	4	1/3	29523W.D50.40	29523W.D50.42	29523W.D50.47
37W	4000k	4699	>80	230	1445	42	9	1/3	29523W.D37.40	29523W.D37.42	29523W.D37.47
55W	4000k	6820	>80	230	1445	42	9	1/3	29523W.D55.40	29523W.D55.42	29523W.D55.47
75W	4000k	9075	>80	230	1445	42	9	1/3	29523W.D75.40	29523W.D75.42	29523W.D75.47

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%

