



Elegant rond mat opaal glazen LED armatuur voor wand of plafondmontage. Verkrijgbaar in vier verschillende diameters. Zeer diffuus en krachtig licht (CRI>80). Alle elektronische componenten op verzinkt stalen behuizing. Aansluiting op voeding via kroonsteen in de behuizing. Invoer voeding via achterzijde van het armatuur met mogelijkheid tot doorlussen. Zeer eenvoudige/veilige montage van diffuser met verende clips - geen gereedschap benodigd. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Elegant round matt glass opal LED luminaire for wall or ceilings. Available in four different diameters. Diffuse light distribution (CRI>80). All electronic components on galvanized steel housing. Connection through the back of the luminaire directly connector block. Suitable for series connection. Easy/safe mounting of glass diffuser with spring clips - no tools required. Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <3. Five years warranty.

| Wattage Watts | Kleur Colour | Lumen* Lumen* | Gewicht (kg) Weight (kg) | Ø (mm) Ø (mm) | H (mm) H (mm) | Artikelnr. Article number |
|------------------|-----------------|------------------|-----------------------------|------------------|------------------|------------------------------|
| 9w | 3000k | 960 | 1 | 260 | 103 | 29637W.A9.30 |
| 9w | 3000k | 960 | 1,3 | 305 | 103 | 29637W.B9.30 |
| 15w | 3000k | 1650 | 1,3 | 305 | 114 | 29637W.B15.30 |
| 9w | 3000k | 960 | 1,8 | 365 | 103 | 29637W.C9.30 |
| 15w | 3000k | 1650 | 1,8 | 365 | 114 | 29637W.C15.30 |
| 9w | 3000k | 960 | 2,4 | 420 | 103 | 29637W.D9.30 |
| 15w | 3000k | 1650 | 2,4 | 420 | 114 | 29637W.D15.30 |
| 9w | 4000k | 1040 | 1 | 260 | 103 | 29637W.A9.40 |
| 9w | 4000k | 1040 | 1,3 | 305 | 103 | 29637W.B9.40 |
| 15w | 4000k | 1800 | 1,3 | 305 | 114 | 29637W.B15.40 |
| 9w | 4000k | 1040 | 1,8 | 365 | 103 | 29637W.C9.40 |
| 15w | 4000k | 1800 | 1,8 | 365 | 114 | 29637W.C15.40 |
| 9w | 4000k | 1040 | 2,4 | 420 | 103 | 29637W.D9.40 |
| 15w | 4000k | 1800 | 2,4 | 420 | 114 | 29637W.D15.40 |

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



29637W.A9.30
9w 3000k 1020lm
ηLB 52%