


Extreem lage inbouw LED downlight (30mm) met zwart gelakte aluminium behuizing (RAL 9005). Zeer hoge kwaliteit LED's met hoge kleurweergave (CRI>80). Speciale combinatie PMMA diffusers voor egale lichtverdeling met 115° uitstralingshoek. Standaard verkrijgbaar in warm wit (3000k) en neutraal wit (4000k). Zeer goed toepasbaar in hallen, trappenhuisen en ruimtes met weinig inbouw ruimte. Wordt geleverd inclusief externe driver. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <2. Vijf jaar garantie.

Extremely shallow recessed LED downlight (30mm) black painted aluminium housing (RAL 9005). Very high quality LEDs with high colour rendering (CRI>80). Due to a special combination of PMMA diffusers the light distributions is very even and has a 115° beam angle. Standard available in warm white (3000k) and neutral white (4000k). Very suitable in toilets, corridors, stairways and rooms with limited build-in height. Delivered including external driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (50.000 hours L80B10). Color stability, Mac Adam <2. Fast and easy mounting with springs. Five years warranty.

Wattage Wattage	Kleur Colour	Lumen* Lumen*	Diameter (mm) Diameter (mm)	Zaagmaat Cutsize	Hoogte(mm) Height(mm)	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikelnr. Article number	Dali Dali
6,5w	3000k	810	90	80	30	0,20	1/3	61371B.30	61371B.32
9w	3000k	1140	122	105	30	0,25	1/3	61372B.30	61372B.32
17w	3000k	2140	175	156	30	0,35	1/3	61373B.30	61373B.32
24w	3000k	2945	175	156	30	0,35	1/3	61374B.30	61374B.32
21w	3000k	2710	225	200	30	0,60	1/3	61375B.30	61375B.32
30w	3000k	3705	225	200	30	0,60	1/3	61376B.30	61376B.32
6,5w	4000k	850	90	80	30	0,20	1/3	61371B.40	61371B.42
9w	4000k	1200	122	105	30	0,25	1/3	61372B.40	61372B.42
17w	4000k	2250	175	156	30	0,35	1/3	61373B.40	61373B.42
24w	4000k	3100	175	156	30	0,35	1/3	61374B.40	61374B.42
21w	4000k	2850	225	200	30	0,60	1/3	61375B.40	61375B.42
30w	4000k	3900	225	200	30	0,60	1/3	61376B.40	61376B.42

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Accessoires:

- Gemonteerde 1,5 meter snoer + stekker (2-polig) _____-K
- Gemonteerde 0,5 meter snoer + GST18i3® male _____-L
- Gemonteerde 2x0,5 meter snoer + GST18i3® male BST14i2 _____-Q

Accessories:

- Assembled 1,5 meter cable + plug (2-pole) _____-K
- Assembled 0,5 meter cable + GST18i3® male _____-L
- Assembled 2x0,5 meter cable + GST18i3® male + BST14i2 _____-Q



61371B.30

6,5W 3000K 810lm
ηLB 100%

