


Lage opbouw LED downlight (90mm) met zwart gelakte aluminium behuizing (RAL 9005). Zeer hoge kwaliteit LED's met hoge kleurweergave (CRI>80). Speciale combinatie PMMA diffusers voor egale lichtverdeling met 115° uitstralingshoek. Standaard verkrijgbaar in warm wit (3000k) en neutraal wit (4000k). Zeer goed toepasbaar in hallen, trappenhuis en ruimtes met minimale opbouw ruimte. Wordt geleverd inclusief interne driver. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <2. Vijf jaar garantie.

Shallow surface mounted LED downlight (90mm) black painted aluminium housing (RAL 9005). Very high quality LEDs with high colour rendering (CRI>80). Due to a special combination of PMMA diffusers the light distributions is very even and has a 115° beam angle. Standard available in warm white (3000k) and neutral white (4000k). Very suitable in toilets, corridors, stairways and rooms with limited height. Delivered including internal driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <2. Five years warranty.

Wattage Wattage	Kleur Colour	Lumen* Lumen*	Diameter (mm) Diameter (mm)	Hoogte(mm) Height(mm)	Gewicht (kg) Weight (kg)	Noodvoorz. (u) Emergency (h)	Artikelnr. Article number	Dali Dali
6,5w	3000k	810	90	90	0,25	1/3	61371BPB.30	61371BPB.32
9w	3000k	1140	122	90	0,35	1/3	61372BPB.30	61372BPB.32
17w	3000k	2140	175	90	0,50	1/3	61373BPB.30	61373BPB.32
24w	3000k	2945	175	90	0,50	1/3	61374BPB.30	61374BPB.32
21w	3000k	2710	225	90	0,75	1/3	61375BPB.30	61375BPB.32
30w	3000k	3705	225	90	0,75	1/3	61376BPB.30	61376BPB.32
6,5w	4000k	850	90	90	0,25	1/3	61371BPB.40	61371BPB.42
9w	4000k	1200	122	90	0,35	1/3	61372BPB.40	61372BPB.42
17w	4000k	2250	175	90	0,50	1/3	61373BPB.40	61373BPB.42
24w	4000k	3100	175	90	0,50	1/3	61374BPB.40	61374BPB.42
21w	4000k	2850	225	90	0,75	1/3	61375BPB.40	61375BPB.42
30w	4000k	3900	225	90	0,75	1/3	61376BPB.40	61376BPB.42

\* Lichtstroom van armatuur, tolerantie van +/- 10%


\* Luminaire luminous flux, tolerance of +/- 10%


**Opties:**

- 2700k of 6000k op aanvraag
- Optioneel doorvoerbedrading (niet mogelijk bij 90, 122 en 175)

**Options:**

- 2700k or 6000k available on request
- Optionally through wiring (not possible with 90, 122 and 175)


**61371BPB.30**

 6,5W 3000K 810lm  
 ηLB 100%