

Epic 65 BLACK SQUARE







Modulaire vierkante vaste miniatuur LED spot. Zwarte behuizing uit gegoten aluminium (RAL9005). Verdiepte lens voor extra hoog comfort en lage UGR (smalle bundels). Standaard geleverd met CRI > 90 (R9 > 80) COB SDCM < 2. Verkrijgbaar met verschillende bundels en met grote keus aan accessoires. Wordt geleverd inclusief externe driver. Snelle en eenvoudige montage met veren. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (L90B10 50.000 uur). Vijf jaar garantie.

Modular square fixed LED spot light. Housing made of die casted black painted aluminium (RAL 9005). Deep baffle with lens for extra comfort and low glare (narrow beam angles). Standard delivered in CRI > 90 (R9 > 80) COB SDCM < 2. Available with different beam angles and large range of accessories. Delivered with external driver. Direct connection to mains. Low maintenance and high life expectancy (50.000 hours L90B10). Fast and easy mounting with springs. Five years warranty.


Wattage Watts	Kleur Colour	Amperage (mA) Amperage (mA)	Lumen* Lumen*	Graden Degree	Gewicht (kg) Weight (kg)	Artikel nr. Article no.	Dali Dali	Casambi Casambi
5w	3000k	150	567	30°	0,3	61502B.053030	61502B.053032	61502B.053035
9w	3000k	250	945	30°	0,3	61502B.093030	61502B.093032	61502B.093035
13w	3000k	350	1324	30°	0,3	61502B.133030	61502B.133032	61502B.133035
5w	3000k	150	623	35°	0,3	61502B.053530	61502B.053532	61502B.053535
9w	3000k	250	1038	35°	0,3	61502B.093530	61502B.093532	61502B.093535
13w	3000k	350	1453	35°	0,3	61502B.133530	61502B.133532	61502B.133535
5w	3000k	150	623	50°	0,3	61502B.055030	61502B.055032	61502B.055035
9w	3000k	250	1038	50°	0,3	61502B.095030	61502B.095032	61502B.095035
13w	3000k	350	1453	50°	0,3	61502B.135030	61502B.135032	61502B.135035
5w	3000k	150	1007	60°	0,3	61502B.060530	61502B.060532	61502B.060535
9w	3000k	250	1007	60°	0,3	61502B.096030	61502B.096032	61502B.096035
13w	3000k	350	1410	60°	0,3	61502B.136030	61502B.136032	61502B.136035
5w	4000k	150	588	30°	0,3	61502B.053040	61502B.053042	61502B.053045
9w	4000k	250	980	30°	0,3	61502B.093040	61502B.093042	61502B.093045
13w	4000k	350	1372	30°	0,3	61502B.133040	61502B.133042	61502B.133045
5w	4000k	150	644	35°	0,3	61502B.053540	61502B.053542	61502B.053545
9w	4000k	250	1073	35°	0,3	61502B.093540	61502B.093542	61502B.093545
13w	4000k	350	1502	35°	0,3	61502B.133540	61502B.133542	61502B.133545
5w	4000k	150	644	50°	0,3	61502B.055040	61502B.055042	61502B.055045
9w	4000k	250	1073	50°	0,3	61502B.095040	61502B.095042	61502B.095045
13w	4000k	350	1502	50°	0,3	61502B.135040	61502B.135042	61502B.135045
5w	4000k	150	1042	60°	0,3	61502B.060540	61502B.060542	61502B.060545
9w	4000k	250	1042	60°	0,3	61502B.096040	61502B.096042	61502B.096045
13w	4000k	350	1459	60°	0,3	61502B.136040	61502B.136042	61502B.136045

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



SPOTS SPOTS




Opties:



- 1,5 meter snoer met 3-polige Schuko stekker
- 0,5 meter snoer + GST18i3® connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3® and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5® Blue connector male (dim)
- IP65 upgrade, ring + helder glas
- Trimless versie

Options:

- 1,5m cable with Schuko 3-pin plug
- 0,5 meter cable + GST18i3® connector (non - dimmable)
- 0,5 meter cable + GST18i3® and BST14i2 connector (dim)
- 0,5 meter cable + GST18i5® Blue connector male (dim)
- IP65 upgrade, ring + clear glass
- Trimless version



trimless version optional



61502B.053030

5w 3000K

567 lumen 30°

melis lighting