


Exo

IP40

Innovatieve LED spot (diameter 52mm) voor vluchtwegen. Verkrijgbaar met cirkel- of corridor-lens. Het alternatief op noodinbouw in downlights, T5 en T8 armaturen. De Exo is voorzien van een 3W CREE powerLED met reflector, elektronica en batterijpack. Deze standalone module treedt in werking zodra de vaste fase onderbroken wordt (optioneel ook schakelbaar leverbaar voor gebruik als orientatieverlichting). Met de krachtige LED kan een oppervlakte van 19m diameter verlicht worden tot 1 lux. Zeer eenvoudig te installeren door middel van scharnierbare noodmodule en batterij. Standaard 3 uur autonomische batterij met AutoTest (optioneel DALI). Garantie 3 jaar.

Innovative LED spot (diameter 52mm) for escape routes. Available with circle or corridor lens. The alternative for integrated emergency units in downlights, T5 or T8 luminaires. The Exo is equipped with a 3W CREE powerLED with reflector, electronics and battery pack. This stand alone module is a non-maintained luminaire that will become operative once the fixed phase is interrupted (optionally avaible in switchable version for use as orientational lighting). This powerful LED can light a surface of 19m diameter at 1 lux. Very simple installation with hinged emergency module and battery. Standard 3 hours autonomic battery with AutoTest. Warranty 3 years.



Cirkel lens *Circle lens*	**Corridor lens** *Corridor lens*	**Artikelnummer** *Article number*	**Artikelnummer Dali** *Article number Dali*
x		29458.R	29458.R.2
	x	29458.C	29458.C.2

Spacingtabel 1 lux CIRKEL LENS / *Spacing table 1 lux CIRCLE LENS*

Hoogte *Height*				
2,0	2,75	6,3	2,75	6,3
2,5	3,09	7,3	3,09	7,3
3,0	3,33	8,24	3,33	8,14
3,5	3,62	8,83	3,62	8,83
4,0	3,73	9,41	3,37	9,41

Spacingtabel 1 lux CORRIDOR LENS / *Spacing table 1 lux CORRIDOR LENS*

Hoogte *Height*					
2,00	1,62	5,32	5,49	14,66	9,60
2,50	1,44	4,88	5,62	15,66	10,51
3,00	1,27	4,46	5,64	16,46	10,27
3,50	1,00	4,11	2,27	15,79	9,99
4,00	0,78	3,91	2,40	13,19	5,51

T +31 (0)13 - 456 39 00 | E info@melis-lighting.nl