Holon 220


Professionele ronde modulaire LED downlight met gesatineerde PS Microprisma afscherming, brede bundel (>69°) en lage verblinding (UGR<20). Dubbele hoog rendement aluminium reflector met facetten. Voorzien van COB LED met hoge lichtopbrengst (max. 134lm/w, **CRI>93 (R9>83)**). Behuizing van verzinkt plaatstaal en verwisselbare aluminium afdekring (RAL 9003). Zeer geschikt als basis verlichting in scholen, museums, kantoren, winkels en ziekenhuizen. Wordt geleverd inclusief externe driver. Directe aansluiting op 220-240VAC. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (L90B10 180.000 uur). Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Professional powerful modular LED downlight with satinated PS Microprism diffuser, wide beam angle (>69°) and low glare (UGR<20). Internal high efficiency aluminum reflector. Integrated COB LED with high output (max. 134lm/w, **CRI>93 (R9>83)**). *Housing made of galvanised sheet metal and white painted (RAL 9003) aluminum trim. Very suitable as general lighting schools, museums, offices and shops. Delivered including external driver. Direct connection to 220-240VAC Fast and easy mounting. Low maintenance and high life expectancy (L90B10 180.000 hours). High color consistency SDCM <2. Five years warranty.*


Wattage *Watts*	**Kleur** *Colour*	**Lumen*** *Lumen**	**CRI** *CRI*	**Amperage (mA)** *Amperage (mA)*	**Gewicht (kg)** *Weight (kg)*	**Noodvoorz. (u)** *Emergency (h)*	**Artikelnr.** *Article number*	**Dimbaar (1-10V)** *Dimmable (1-10V)*	**Dali-2** *Dali-2*
5w	3000k	632	>93	150	2,7	1/3	21018WS.0030	21018WS.0130	21018WS.0230
8w	3000k	1049	>93	250	2,7	1/3	21018W.0030	21018W.0130	21018W.0230
12w	3000k	1455	>93	350	2,7	1/3	20017W.0030	20017W.0130	20017W.0230
17w	3000k	2047	>93	500	2,7	1/3	21010W.0030	21010W.0130	21010W.0230
25w	3000k	2798	>93	700	2,7	1/3	20019W.0030	20019W.0130	20019W.0230
33w	3000k	3511	>93	900	2,7	1/3	21011W.0030	21011W.0130	21011W.0230
39w	3000k	3993	>93	1050	2,7	1/3	21013W.0030	21013W.0130	21013W.0230
5w	4000k	632	>93	150	2,7	1/3	21018WS.0040	21018WS.0140	21018WS.0240
8w	4000k	1049	>93	250	2,7	1/3	21018W.0040	21018W.0140	21018W.0240
12w	4000k	1455	>93	350	2,7	1/3	20017W.0040	20017W.0140	20017W.0240
17w	4000k	2047	>93	500	2,7	1/3	21010W.0040	21010W.0140	21010W.0240
25w	4000k	2798	>93	700	2,7	1/3	20019W.0040	20019W.0140	20019W.0240
33w	4000k	3511	>93	900	2,7	1/3	21011W.0040	21011W.0140	21011W.0240
39w	4000k	3993	>93	1050	2,7	1/3	21013W.0040	21013W.0140	21013W.0240

* Lichtstroom van armatuur, tolerantie van +/- 10%


* *Luminaire luminous flux, tolerance of +/- 10%*











20018WS.0030
5W 3000k 632lm
ηLB 100%

Opties:
- 1,5 meter snoer met 3-polige Shuko stekker
- 0,5 meter snoer + GST18i3® connector (niet - dimbaar)
- 0,5 meter snoer + GST18i3® and BST14i2 connector (dim)
- 0,5 meter snoer + GST18i5® Blue connector male (dim)
- Andere RAL kleur
- 2700K, 3500k, 5000k of hogere CRI waarde 90/97
- Vlees, brood of Crisp White

Options:
- *1,5m cable with Shuko 3-pin plug*
- *0,5 meter cable + GST18i3® connector (non - dimmable)*
- *0,5 meter cable + GST18i3® and BST14i2 connector (dim)*
- *0,5 meter cable + GST18i5® Blue connector male (dim)*
- *Different RAL color*
- *2700k, 3500k, 5000k or higher CRI values 90/97*
- *Meat, bread or Crisp White*

melis lighting