

# Holon 260-235 DARKLIGHT SUSPENDED




Extreem krachtige ronde LED pendel downlight met hoog rendement. Voorzien van trompetvormige darklight reflector van hoogglans 99,98% aluminium met brede bundel (>60°). Zeer lage verblinding (UGR 17) en minimale helderheid door uniek darklight reflector ontwerp. Voorzien van passieve waterkoeling met heatpipe. Wit gelakte (RAL 9003) metalen behuizing en aluminium sierrand (optioneel zilver grijs). Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer goed toepasbaar in vides, kerken en moskeeën. Inclusief 3m snoer en staal kabels (3x). Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L80B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Extremely powerful round suspended LED downlight with high efficacy. Trumpet shaped darklight reflector made of 99,98% anodised specular aluminium with wide beam angle (>60°). Very low glare (UGR 17) and minimal brightness due to unique darklight reflector design. Internal passive water cooling with heatpipe technology. White painted die cast aluminium body (RAL9003). Delivered including internal driver. Direct connection to mains. Ideal for lighting high rooms like lobby's, churches and mosques. Including 3 meter cable and steel wires (3x) Low maintenance and high life expectancy (50.000 hours L80B10). Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Artikel nr. Article no.	Dali Dali
18w	3000k	2420	350	6	23011WPN.18.30	23011WPN.18.32
25w	3000k	3260	500	6	23011WPN.25.30	23011WPN.25.32
33w	3000k	4030	700	6	23011WPN.33.30	23011WPN.33.32
45w	3000k	5100	900	6	23011WPN.45.30	23011WPN.45.32
54w	3000k	5760	1050	6	23011WPN.54.30	23011WPN.54.32
62w	3000k	6370	1200	6	23011WPN.62.30	23011WPN.62.32
69w	3000k	6845	1300	6	23011WPN.69.30	23011WPN.69.32
18w	4000k	2545	350	6	23011WPN.18.40	23011WPN.18.42
25w	4000k	3430	500	6	23011WPN.25.40	23011WPN.25.42
33w	4000k	4240	700	6	23011WPN.33.40	23011WPN.33.42
45w	4000k	5380	900	6	23011WPN.45.40	23011WPN.45.42
54w	4000k	6070	1050	6	23011WPN.54.40	23011WPN.54.42
62w	4000k	6700	1200	6	23011WPN.62.40	23011WPN.62.42
69w	4000k	7200	1300	6	23011WPN.69.40	23011WPN.69.42

\* Lichtstroom van armatuur, tolerantie van +/- 10%

\* Luminaire luminous flux, tolerance of +/- 10%



PENDEL ARMATUREN SUSPENDED LUMINAIRES




**Opties:**

- 2700k
- 90CRI of 97CRI

**Opties:**

- 2700k
- 90CRI or 97CRI



**23011WPN.25.40**

25w 4000k 3430lm  
ηLB 81,0%

**melis lighting**