Marici 130-140 Facet Track

Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van decoratieve aluminium (99,9%) semi hoogglans facet reflector met brede uitstraling >71,1° (UGR<19 - <1800lm) en hoge efficiency (max 161lm/w) met **CRI>93 (R9>88)**. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (L90B10 180.000 uur). Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Round LED downlight with adapter for 3-phase track systems. Semi specular faceted aluminum reflector (99,9%) with wide beam angle >71,1° (UGR<19 - <1800lm) and high efficiency (max 161lm/w) with **CRI>93 (R9>88)**. *White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (L90B10 180.000 hours). High color consistency SDCM <2. Five years warranty.*

Wattage Watts	**Kleur** Colour	**Lumen*** Lumen*	**CRI** CRI	**Amperage (mA)** Amperage (mA)	**kg** kg	**Noodvoorz. (u)** Emergency (h)	**Artikel nr.** Article no.	**Dimbaar (1-10V)** Dimmable (1-10V)	**Dali-2** Dali-2	**Casambi** Casambi
5w	3000k	804	>93	150	1,2	1/3	23008WT.05.30F	23008WT.05.31F	23008WT.05.32F	23008WT.05.35F
9w	3000k	1335	>93	250	1,2	1/3	23008WT.09.30F	23008WT.09.31F	23008WT.09.32F	23008WT.09.35F
13w	3000k	1851	>93	350	1,2	1/3	23008WT.13.30F	23008WT.13.31F	23008WT.13.32F	23008WT.13.35F
19w	3000k	2605	>93	500	1,2	1/3	23008WT.19.30F	23008WT.19.31F	23008WT.19.32F	23008WT.19.35F
5w	4000k	804	>93	150	1,2	1/3	23008WT.05.40F	23008WT.05.41F	23008WT.05.42F	23008WT.05.45F
9w	4000k	1335	>93	250	1,2	1/3	23008WT.09.40F	23008WT.09.41F	23008WT.09.42F	23008WT.09.45F
13w	4000k	1851	>93	350	1,2	1/3	23008WT.13.40F	23008WT.13.41F	23008WT.13.42F	23008WT.13.45F
19w	4000k	2605	>93	500	1,2	1/3	23008WT.19.40F	23008WT.19.41F	23008WT.19.42F	23008WT.19.45F

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*









Accessoires:
- 3-fase rails en connectors

Opties:
- Vlees, Brood of Crisp white (2700k, 3000k of 3500k)

Accessories:
- 3-phase tracks and connectors

Opties:
- *Meat, Bread or Crisp white*
- *(2700k, 3000k or 3500k)*



23008WT.05.30F
5w 804lm 3000K
ηLB 100%

melis lighting