

Marici 130-140 Matt Track

Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van hoogwaardige aluminium (99,9%) matte reflector (UGR<21). Zeer brede bundel (>73,0°) en hoge efficiency (max 117lm/w) met **CRI>93**. Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Onderhoudsarm en hoge levensduurverwachting. Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.





Round LED downlight with adapter for 3-phase track systems. High gloss aluminium reflector (99,9%) with matt finish (UGR<21). Extra wide beam angle (>73,0°) and high efficiency (max 117lm/w) with **CRI>93**. Satinated PS Microprism diffuser for high comfort. White painted steel (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to mains. Low maintenance and high life expectancy. High color consistency SDCM <2. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Amperage (mA) Amperage (mA)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali-2 Dali-2	Casambi Casambi
5w	3000k	565	>93	140	1,2	1/3	23008WT.05.30M	23008WT.05.31M	23008WT.05.32M	23008WT.05.35M
9w	3000k	938	>93	250	1,2	1/3	23008WT.09.30M	23008WT.09.31M	23008WT.09.32M	23008WT.09.35M
13w	3000k	1301	>93	350	1,2	1/3	23008WT.13.30M	23008WT.13.31M	23008WT.13.32M	23008WT.13.35M
19w	3000k	1830	>93	500	1,2	1/3	23008WT.19.30M	23008WT.19.31M	23008WT.19.32M	23008WT.19.35M
27w	3000k	2501	>93	700	1,2	1/3	23008WT.27.30M	23008WT.27.31M	23008WT.27.32M	23008WT.27.35M
5w	4000k	565	>93	140	1,2	1/3	23008WT.05.40M	23008WT.05.41M	23008WT.05.42M	23008WT.05.45M
9w	4000k	938	>93	250	1,2	1/3	23008WT.09.40M	23008WT.09.41M	23008WT.09.42M	23008WT.09.45M
13w	4000k	1301	>93	350	1,2	1/3	23008WT.13.40M	23008WT.13.41M	23008WT.13.42M	23008WT.13.45M
19w	4000k	1830	>93	500	1,2	1/3	23008WT.19.40M	23008WT.19.41M	23008WT.19.42M	23008WT.19.45M
27w	4000k	2501	>93	700	1,2	1/3	23008WT.27.40M	23008WT.27.41M	23008WT.27.42M	23008WT.27.45M

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



TRACK SYSTEEM TRACK SYSTEM




Accessoires:
- 3-fase rails en connectors

Opties:
- Vlees, Brood of Crisp white
(2700k, 3000k of 3500k)

Accessories:
- 3-phase tracks and connectors

Opties:
- Meat, Bread or Crisp white
- (2700k, 3000k or 3500k)

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
5	73.000
9	70.000
13	60.000
19	53.000



23008WT.5.30M
5w 565lm 3000K
ηLB 100%