


Ronde LED pendel downlight. Voorzien van trompetvormige darklight reflector van 99,98% hoogglans aluminium met medium bundel (>50°) en hoge efficiency (max 147lm/w) met CRI>80. Zeer lage verblinding (UGR<19) en minimale helderheid door uniek darklight reflector ontwerp. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver en 3 meter snoer. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round suspended LED downlight. Trumpet shaped darklight reflector made of 99,98% specular aluminium with medium beam angle (>50°) and high efficiency (max 147lm/w) with CRI>80. Very low glare (UGR<19) and minimal brightness due to unique darklight reflector design. White painted steel body (RAL9003). Delivered including internal driver and 3 meter cable. Direct connection to 220-240VAC. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
5w	3000k	747	140	1,4	23007WPN.05.30	23007WPN.05.31	23007WPN.05.32	23007WPN.05.35
9w	3000k	1202	250	1,4	23007WPN.09.30	23007WPN.09.31	23007WPN.09.32	23007WPN.09.35
13w	3000k	1629	350	1,4	23007WPN.13.30	23007WPN.13.31	23007WPN.13.32	23007WPN.13.35
19w	3000k	2227	500	1,4	23007WPN.19.30	23007WPN.19.31	23007WPN.19.32	23007WPN.19.35
5w	4000k	781	140	1,4	23007WPN.05.40	23007WPN.05.41	23007WPN.05.42	23007WPN.05.45
9w	4000k	1262	250	1,4	23007WPN.09.40	23007WPN.09.41	23007WPN.09.42	23007WPN.09.45
13w	4000k	1709	350	1,4	23007WPN.13.40	23007WPN.13.41	23007WPN.13.42	23007WPN.13.45
19w	4000k	2329	500	1,4	23007WPN.19.40	23007WPN.19.41	23007WPN.19.42	23007WPN.19.45

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



Opties:


- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI

Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren)
Life expectancy (hours)

Watt	L90B10
5	73.000
9	70.000
13	60.000
19	53.000



23007WPN.05.30

5w 3000k 747lm
ηLB 84%