

Marici 130-140 MATT SUSPENDED



PENDEL ARMATUREN SUSPENDED LUMINAIRES


Ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) matte reflector (UGR<21). Gesatineerde PS Microprisma afscherming voor extra comfort. Brede bundel (>73,0°) en hoge efficiency (max 127lm/w) met CRI>80. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round suspended LED downlight. High gloss aluminium reflector (99,9%) with matt finish (UGR<21). Wide beam angle (>77,0°) and high efficiency (max 127lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
5w	3000k	635	140	1,4	23008WPN.05.30M	23008WPN.05.31M	23008WPN.05.32M	23008WPN.05.35M
9w	3000k	1025	250	1,4	23008WPN.09.30M	23008WPN.09.31M	23008WPN.09.32M	23008WPN.09.35M
13w	3000k	1390	350	1,4	23008WPN.13.30M	23008WPN.13.31M	23008WPN.13.32M	23008WPN.13.35M
19w	3000k	1900	500	1,4	23008WPN.19.30M	23008WPN.19.31M	23008WPN.19.32M	23008WPN.19.35M
5w	4000k	665	140	1,4	23008WPN.05.40M	23008WPN.05.41M	23008WPN.05.42M	23008WPN.05.45M
9w	4000k	1075	250	1,4	23008WPN.09.40M	23008WPN.09.41M	23008WPN.09.42M	23008WPN.09.45M
13w	4000k	1460	350	1,4	23008WPN.13.40M	23008WPN.13.41M	23008WPN.13.42M	23008WPN.13.45M
19w	4000k	1985	500	1,4	23008WPN.19.40M	23008WPN.19.41M	23008WPN.19.42M	23008WPN.19.45M

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



Opties:


- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI

Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren) Life expectancy (hours)

Watt	L90B10
5	73.000
9	70.000
13	60.000
19	53.000



23008WPN.13.30M
13w 3000k 1390lm
ηLB 72%

melis lighting