

Marici 130-140 SPECULAR SUSPENDED




Ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<18).
Gesatineerde PS Microprisma afscherming voor extra comfort.
Brede bundel (>77,0°) en hoge efficiency (max 135lm/w) met **CRI>93 (R9>83)**. Wit gelakte (RAL 9003) stalen behuizing.
Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer.
Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Hoge kleurconsistentie SDCM <2.
Vijf jaar garantie.

Round suspended LED downlight. High gloss aluminium reflector (99,9%) with specular finish (UGR<22). Wide beam angle (>77,0°) and high efficiency (max 135lm/w) with **CRI>93 (R9>83)**. Saturated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy. High color consistency SDCM <2. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Amperage (mA) Amperage (mA)	kg kg	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali-2 Dali-2	Casambi Casambi
5w	3000k	657	>93	150	1,4	23008WPN.05.30	23008WPN.05.31	23008WPN.05.32	23008WPN.05.35
9w	3000k	1090	>93	250	1,4	23008WPN.09.30	23008WPN.09.31	23008WPN.09.32	23008WPN.09.35
13w	3000k	1513	>93	350	1,4	23008WPN.13.30	23008WPN.13.31	23008WPN.13.32	23008WPN.13.35
19w	3000k	2128	>93	500	1,4	23008WPN.19.30	23008WPN.19.31	23008WPN.19.32	23008WPN.19.35
5w	4000k	657	>93	150	1,4	23008WPN.05.40	23008WPN.05.41	23008WPN.05.42	23008WPN.05.45
9w	4000k	1090	>93	250	1,4	23008WPN.09.40	23008WPN.09.41	23008WPN.09.42	23008WPN.09.45
13w	4000k	1513	>93	350	1,4	23008WPN.13.40	23008WPN.13.41	23008WPN.13.42	23008WPN.13.45
19w	4000k	2128	>93	500	1,4	23008WPN.19.40	23008WPN.19.41	23008WPN.19.42	23008WPN.19.45

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



PENDEL ARMATUREN *SUSPENDED LUMINAIRES*




Opties:

- Vlees, Brood of Crisp white
- 2700k of 3500k

Opties:

- Meat, Bread or Crisp white
- 2700k or 3500k

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
5	73.000
9	70.000
13	60.000
19	53.000



23008WPN.05.30

5w 3000k 657lm
ηLB 100%

melis lighting