

Marici 130-140 SPECULAR SUSPENDED




Ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<18). Gesatineerde PS Microprisma afscherming voor extra comfort. Brede bundel (>77,0°) en hoge efficiency (max 134lm/w) met CRI>80. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer en staal kabels (3x). Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round suspended LED downlight. High gloss aluminium reflector (99,9%) with specular finish (UGR<22). Wide beam angle (>77,0°) and high efficiency (max 134lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable and steel wires (3x) Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
5w	3000k	670	140	1,4	23008WPN.05.30	23008WPN.05.31	23008WPN.05.32	23008WPN.05.35
9w	3000k	1080	250	1,4	23008WPN.09.30	23008WPN.09.31	23008WPN.09.32	23008WPN.09.35
13w	3000k	1465	350	1,4	23008WPN.13.30	23008WPN.13.31	23008WPN.13.32	23008WPN.13.35
19w	3000k	2005	500	1,4	23008WPN.19.30	23008WPN.19.31	23008WPN.19.32	23008WPN.19.35
5w	4000k	700	140	1,4	23008WPN.05.40	23008WPN.05.41	23008WPN.05.42	23008WPN.05.45
9w	4000k	1135	250	1,4	23008WPN.09.40	23008WPN.09.41	23008WPN.09.42	23008WPN.09.45
13w	4000k	1540	350	1,4	23008WPN.13.40	23008WPN.13.41	23008WPN.13.42	23008WPN.13.45
19w	4000k	2100	500	1,4	23008WPN.19.40	23008WPN.19.41	23008WPN.19.42	23008WPN.19.45

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



PENDEL ARMATUREN / SUSPENDED LUMINAIRES



Opties:


- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI

Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren) Life expectancy (hours)

Watt	L90B10
5	73.000
9	70.000
13	60.000
19	53.000



23008WPN.13.40

13w 4000k 1540lm
ηLB 76%