Marici 130-140 WHITE SUSPENDED

Ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) witte reflector (UGR<21). Brede bundel (>66,0°) en hoge efficiency (max 117lm/w) met **CRI>93 (R9>83)**. Gesatineerde PS Microprisma afscherming voor extra comfort. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (L90B10 180.000 uur). Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Round suspended LED downlight. High gloss aluminium reflector (99,9%) with white finish (UGR<21). Wide beam angle (>66,0°) and high efficiency (max 117lm/w) with **CRI>93 (R9>83)**. *Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy (L90B10 180.000 hours). High color consistency SDCM <2. Five years warranty.*

Wattage *Watts*	**Kleur** *Colour*	**Lumen*** *Lumen**	**CRI** *CRI*	**Amperage (mA)** *Amperage (mA)*	**kg** kg	**Artikel nr.** *Article no.*	**Dimbaar (1-10V)** *Dimmable (1-10V)*	**Dali-2** *Dali-2*	**Casambi** *Casambi*
5w	3000k	569	>93	150	1,4	23008WPN.05.30W	23008WPN.05.31W	23008WPN.05.32W	23008WPN.05.35W
9w	3000k	945	>93	250	1,4	23008WPN.09.30W	23008WPN.09.31W	23008WPN.09.32W	23008WPN.09.35W
13w	3000k	1310	>93	350	1,4	23008WPN.13.30W	23008WPN.13.31W	23008WPN.13.32W	23008WPN.13.35W
19w	3000k	1843	>93	500	1,4	23008WPN.19.30W	23008WPN.19.31W	23008WPN.19.32W	23008WPN.19.35W
5w	4000k	569	>93	150	1,4	23008WPN.05.40W	23008WPN.05.41W	23008WPN.05.42W	23008WPN.05.45W
9w	4000k	945	>93	250	1,4	23008WPN.09.40W	23008WPN.09.41W	23008WPN.09.42W	23008WPN.09.45W
13w	4000k	1310	>93	350	1,4	23008WPN.13.40W	23008WPN.13.41W	23008WPN.13.42W	23008WPN.13.45W
19w	4000k	1843	>93	500	1,4	23008WPN.19.40W	23008WPN.19.41W	23008WPN.19.42W	23008WPN.19.45W

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*









Opties:
- Vlees, Brood of Crisp white
- 2700k of 3500k

Opties:
- Meat, Bread or Crisp white
- 2700k or 3500k



23008WPN.05.30W
5w 3000k 569lm
ηLB 100%

melis lighting