

Marici 130-140 WHITE SUSPENDED



PENDEL ARMATUREN SUSPENDED LUMINAIRES


Ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) witte reflector (UGR<21). Brede bundel (>66,0°) en hoge efficiency (max 126lm/w) met CRI>80. Gesatineerde PS Microprisma afscherming voor extra comfort. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round suspended LED downlight. High gloss aluminium reflector (99,9%) with white finish (UGR<21). Wide beam angle (>66,0°) and high efficiency (max 126lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
5w	3000k	630	140	1,4	23008WPN.05.30W	23008WPN.05.31W	23008WPN.05.32W	23008WPN.05.35W
9w	3000k	1010	250	1,4	23008WPN.09.30W	23008WPN.09.31W	23008WPN.09.32W	23008WPN.09.35W
13w	3000k	1370	350	1,4	23008WPN.13.30W	23008WPN.13.31W	23008WPN.13.32W	23008WPN.13.35W
19w	3000k	1875	500	1,4	23008WPN.19.30W	23008WPN.19.31W	23008WPN.19.32W	23008WPN.19.35W
5w	4000k	655	140	1,4	23008WPN.05.40W	23008WPN.05.41W	23008WPN.05.42W	23008WPN.05.45W
9w	4000k	1060	250	1,4	23008WPN.09.40W	23008WPN.09.41W	23008WPN.09.42W	23008WPN.09.45W
13w	4000k	1435	350	1,4	23008WPN.13.40W	23008WPN.13.41W	23008WPN.13.42W	23008WPN.13.45W
19w	4000k	1960	500	1,4	23008WPN.19.40W	23008WPN.19.41W	23008WPN.19.42W	23008WPN.19.45W

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



Opties:


- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI

Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren)
Life expectancy (hours)

Watt	L90B10
5	73.000
9	70.000
13	60.000
19	53.000



23008WPN.09.40W

9w 4000k 1060lm
ηLB 71%

melis lighting