

# Marici 130-140 Specular Track




Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van hoogwaardige aluminium (99,9%) hoogglans reflector (UGR<18). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (>77,0°) en hoge efficiency (max 134lm/w) met CRI>80. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with adapter for 3-phase track systems. High gloss aluminium reflector (99,9%) with specular finish (UGR<18). Extra wide beam angle (>77,0°) and high efficiency (max 134lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to mains. Low maintenance and high life expectancy. Color stability, Mac Adam <3. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	Gewicht (kg) Weight (kg)	Artikel nr. Article no.	Dali Dali	Casambi Casambi
5w	3000k	670	140	1,2	23008WT.05.30	23008WT.05.32	23008WT.05.35
9w	3000k	1080	250	1,2	23008WT.09.30	23008WT.09.32	23008WT.09.35
13w	3000k	1465	350	1,2	23008WT.13.30	23008WT.13.32	23008WT.13.35
19w	3000k	2005	500	1,2	23008WT.19.30	23008WT.19.32	23008WT.19.35
5w	4000k	700	140	1,2	23008WT.05.40	23008WT.05.42	23008WT.05.45
9w	4000k	1135	250	1,2	23008WT.09.40	23008WT.09.42	23008WT.09.45
13w	4000k	1540	350	1,2	23008WT.13.40	23008WT.13.42	23008WT.13.45
19w	4000k	2100	500	1,2	23008WT.19.40	23008WT.19.42	23008WT.19.45

\* Lichtstroom van armatuur, tolerantie van +/- 10%

\* Luminaire luminous flux, tolerance of +/- 10%



TRACK SYSTEEM TRACK SYSTEM



#### Accessoires:

- 3-fase rails en connectors

#### Opties:

- Vlees, Brood of Crisp white  
(2700k, 3000k of 3500k)  
- 90CRI of 97CRI

#### Accessories:

- 3-phase tracks and connectors


#### Opties:

- Meat, Bread or Crisp white  
(2700k, 3000k or 3500k)  
- 90CRI or 97CRI

#### Levensduurverwachting (uren)

Life expectancy (hours)

Watt	L90B10
5	73.000
9	70.000
13	60.000
19	53.000



#### 23008WT.13.30

13w 1465lm 3000K  
ηLB 76%

melis lighting