

Marici 130-140 Specular

Ronde LED opbouw downlight. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<18). Brede bundel (>77,0°) en hoge efficiency (max 135lm/w) met **CRI>93**. Gesatineerde PS Microprisma afscherming voor extra comfort. Wit gelakte (RAL 9003) stalen behuizing. Zeer geschikt als basis verlichting in gangen of kantoren. Wordt geleverd inclusief interne driver met mogelijkheid tot doorlussen. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting. Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Round surface mounted LED downlight. High gloss aluminium reflector (99,9%) with specular finish (UGR<18). Wide beam angle (>77,0°) and high efficiency (max 135lm/w) with **CRI>93**. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver with possibility for through-wiring. Direct connection to 220-240VAC. Low maintenance and high life expectancy. High color consistency SDCM <2. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Amperage (mA) Amperage (mA)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali-2 Dali-2	Casambi Casambi
5w	3000k	657	>93	140	0,6	1/3	23008WPB.05.30	23008WPB.05.31	23008WPB.05.32	23008WPB.05.35
9w	3000k	1090	>93	250	0,6	1/3	23008WPB.09.30	23008WPB.09.31	23008WPB.09.32	23008WPB.09.35
13w	3000k	1513	>93	350	0,6	1/3	23008WPB.13.30	23008WPB.13.31	23008WPB.13.32	23008WPB.13.35
19w	3000k	2128	>93	500	0,6	1/3	23008WPB.19.30	23008WPB.19.31	23008WPB.19.32	23008WPB.19.35
5w	4000k	657	>93	140	0,6	1/3	23008WPB.05.40	23008WPB.05.41	23008WPB.05.42	23008WPB.05.45
9w	4000k	1090	>93	250	0,6	1/3	23008WPB.09.40	23008WPB.09.41	23008WPB.09.42	23008WPB.09.45
13w	4000k	1513	>93	350	0,6	1/3	23008WPB.13.40	23008WPB.13.41	23008WPB.13.42	23008WPB.13.45
19w	4000k	2128	>93	500	0,6	1/3	23008WPB.19.40	23008WPB.19.41	23008WPB.19.42	23008WPB.19.45

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



OPBOUW DOWNLIGHTS

SURFACE MOUNTED DOWNLIGHTS




Opties:

- Vlees, Brood of Crisp white (2700k of 3500k)
- Schuinstelling voor aflopende plafonds op aanvraag
- Andere RAL kleur

Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- Diagonal attachment for sloped ceilings on request
- Different RAL Colour

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
5	73.000
9	70.000
13	60.000
19	53.000



23008WPB.05.30

5w 3000k 657lm
ηLB 100%