

Marici 130-140 White Track



TRACK SYSTEEM TRACK SYSTEM



Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van decoratieve aluminium (99,9%) wit gelakte reflector met brede uitstraling >66°, (UGR<21) en hoge efficiency (max 126lm/w) met CRI>80. Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with adapter for 3-phase track systems. White painted aluminium reflector (99,9%) with wide beam angle >66°, (UGR<21) and high efficiency (max 126lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Artikel nr. Article no.	Dali Dali	Casambi Casambi
5w	3000k	630	140	1,2	23008WT.05.30W	23008WT.05.32W	23008WT.05.35W
9w	3000k	1010	250	1,2	23008WT.09.30W	23008WT.09.32W	23008WT.09.35W
13w	3000k	1370	350	1,2	23008WT.13.30W	23008WT.13.32W	23008WT.13.35W
19w	3000k	1875	500	1,2	23008WT.19.30W	23008WT.19.32W	23008WT.19.35W
5w	4000k	655	140	1,2	23008WT.05.40W	23008WT.05.42W	23008WT.05.45W
9w	4000k	1060	250	1,2	23008WT.09.40W	23008WT.09.42W	23008WT.09.45W
13w	4000k	1435	350	1,2	23008WT.13.40W	23008WT.13.42W	23008WT.13.45W
19w	4000k	1960	500	1,2	23008WT.19.40W	23008WT.19.42W	23008WT.19.45W

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



Accessoires:

- 3-fase rails en connectors

Opties:

- Vlees, Brood of Crisp white
(2700k, 3000k of 3500k)
- 90CRI of 97CRI


Accessories:

- 3-phase tracks and connectors

Opties:

- Meat, Bread or Crisp white
(2700k, 3000k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
5	73.000
9	70.000
13	60.000
19	53.000



23008WT.13.30W
13w 1370lm 3000K
ηLB 71%

melis lighting