Marici 160-150 Matt Track

Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van decoratieve aluminium (99,9%) matte reflector (UGR<22) met brede uitstraling (>77°) en hoge efficiency (max 150lm/w) met **CRI>93 (R9>83)**. Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (L90B10 180.000 uur). Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Round LED downlight with adapter for 3-phase track systems. Matt aluminium reflector (99,9%) (UGR<22) with wide beam angle (>77°) and high efficiency (max 150lm/w) with ***CRI>93 (R9>83)****. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (L90B10 180.000 hours). High color consistency SDCM <2. Five years warranty.*

Wattage Watts	**Kleur** Colour	**Lumen*** Lumen*	**CRI** CRI	**Amperage (mA)** Amperage (mA)	**kg** kg	**Artikel nr.** Article no.	**Dimbaar (1-10V)** Dimmable (1-10V)	**Dali-2** Dali-2	**Casambi** Casambi
5w	3000k	594	>93	150	1,6	23013WT.05.30M	23013WT.05.31M	23013WT.05.32M	23013WT.05.35M
9w	3000k	986	>93	250	1,6	23013WT.09.30M	23013WT.09.31M	23013WT.09.32M	23013WT.09.35M
12w	3000k	1368	>93	350	1,6	23013WT.12.30M	23013WT.12.31M	23013WT.12.32M	23013WT.12.35M
18w	3000k	1924	>93	500	1,6	23013WT.18.30M	23013WT.18.31M	23013WT.18.32M	23013WT.18.35M
26w	3000k	2630	>93	700	1,6	23013WT.26.30M	23013WT.26.31M	23013WT.26.32M	23013WT.26.35M
5w	4000k	594	>93	150	1,6	23013WT.05.40M	23013WT.05.41M	23013WT.05.42M	23013WT.05.45M
9w	4000k	986	>93	250	1,6	23013WT.09.40M	23013WT.09.41M	23013WT.09.42M	23013WT.09.45M
12w	4000k	1368	>93	350	1,6	23013WT.12.40M	23013WT.12.41M	23013WT.12.42M	23013WT.12.45M
18w	4000k	1924	>93	500	1,6	23013WT.18.40M	23013WT.18.41M	23013WT.18.42M	23013WT.18.45M
26w	4000k	2630	>93	700	1,6	23013WT.26.40M	23013WT.26.41M	23013WT.26.42M	23013WT.26.45M

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*







TRACK SYSTEEM *TRACK SYSTEM*



Accessoires:
- 3-fase rails en connectors

Opties:
- Vlees, Brood of Crisp white 2700k, 3000k of 3500k

Accessories:
- *3-phase tracks and connectors*

Opties:
- *Meat, Bread or Crisp white*
- *2700k, 3000k or 3500k*



23013WT.05.30M
5w 594lm 3000K
ηLB 100%

melis lighting