

Marici 160-150 Matt Track




Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van decoratieve aluminium (99,9%) matte reflector (UGR<22) met brede uitstraling (>77°) en hoge efficiency (max 125lm/w) met CRI>80. Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with adapter for 3-phase track systems. Matt aluminium reflector (99,9%) (UGR<22) with wide beam angle (>77°) and high efficiency (max 125lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Artikel nr. Article no.	Dali Dali	Casambi Casambi
9w	3000k	1125	250	1,6	23013WT.09.30M	23013WT.09.32M	23013WT.09.35M
12w	3000k	1565	350	1,6	23013WT.12.30M	23013WT.12.32M	23013WT.12.35M
18w	3000k	2190	500	1,6	23013WT.18.30M	23013WT.18.32M	23013WT.18.35M
25w	3000k	2990	700	1,6	23013WT.25.30M	23013WT.25.32M	23013WT.25.35M
9w	4000k	1185	250	1,6	23013WT.09.40M	23013WT.09.42M	23013WT.09.45M
12w	4000k	1645	350	1,6	23013WT.12.40M	23013WT.12.42M	23013WT.12.45M
18w	4000k	2300	500	1,6	23013WT.18.40M	23013WT.18.42M	23013WT.18.45M
25w	4000k	3140	700	1,6	23013WT.25.40M	23013WT.25.42M	23013WT.25.45M

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



TRACK SYSTEME TRACK SYSTEM



Accessoires:

- 3-fase rails en connectors

Opties:

- Vlees, Brood of Crisp white
(2700k, 3000k of 3500k)
- 90CRI of 97CRI


Accessories:

- 3-phase tracks and connectors

Opties:

- Meat, Bread or Crisp white
(2700k, 3000k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
9	79.000
12	78.000
18	70.000
25	64.000



23013WT.12.30M
12w 1565lm 3000K
ηLB 74%

melis lighting