


Ronde LED pendel downlight. Voorzien van trompetvormige darklight reflector van 99,98% hoogglans aluminium met medium bundel (>50°). Zeer lage verblinding (UGR<19, 5-18w) en minimale helderheid door uniek darklight reflector ontwerp. Uitgerust met hoge efficiency (max 149lm/w) CRI>80. Wit (RAL 9003) gelakte stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer goed toepasbaar in vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round suspended LED downlight. Trumpet shaped darklight reflector made of 99,98% specular aluminium with medium beam angle (>50°). Very low glare (UGR<19, 5-18w) and minimal brightness due to unique darklight reflector design. Equipped with high efficiency (max 149lm/w) CRI>80. White painted steel body (RAL9003). Delivered including internal driver and connector block. Direct connection to mains. Ideal for lighting high rooms like lobby's, churches and mosques. Delivered including 3 meter cable. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
5w	3000k	802	150	1,6	23006WPN.05.30	23006WPN.05.31	23006WPN.05.32	23006WPN.05.35
9w	3000k	1333	250	1,6	23006WPN.09.30	23006WPN.09.31	23006WPN.09.32	23006WPN.09.35
12w	3000k	1855	350	1,6	23006WPN.12.30	23006WPN.12.31	23006WPN.12.32	23006WPN.12.35
18w	3000k	2596	500	1,6	23006WPN.18.30	23006WPN.18.31	23006WPN.18.32	23006WPN.18.35
25w	3000k	3545	700	1,6	23006WPN.25.30	23006WPN.25.31	23006WPN.25.32	23006WPN.25.35
5w	4000k	842	150	1,6	23006WPN.05.40	23006WPN.05.41	23006WPN.05.42	23006WPN.05.45
9w	4000k	1403	250	1,6	23006WPN.09.40	23006WPN.09.41	23006WPN.09.42	23006WPN.09.45
12w	4000k	1951	350	1,6	23006WPN.12.40	23006WPN.12.41	23006WPN.12.42	23006WPN.12.45
18w	4000k	2727	500	1,6	23006WPN.18.40	23006WPN.18.41	23006WPN.18.42	23006WPN.18.45
25w	4000k	3723	700	1,6	23006WPN.25.40	23006WPN.25.41	23006WPN.25.42	23006WPN.25.45

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




Opties:

- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI

Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
5	80.000
9	79.000
12	78.000
18	70.000
25	64.000



23006WPN.05.40

5w 3000k 802lm
ηLB 88%