

Marici 160-150 MATT SUSPENDED



PENDEL ARMATUREN SUSPENDED LUMINAIRES


Ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) matte reflector (UGR<22). Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer brede bundel (>77,0°) en hoge efficiency (max 125lm/w) met CRI>80. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round suspended LED downlight. High gloss aluminium reflector (99,9%) with matt finish (UGR<22). Extra wide beam angle (>77,0°) and high efficiency (max 125lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
9w	3000k	1125	250	1,8	23013WPN.09.30M	23013WPN.09.31M	23013WPN.09.32M	23013WPN.09.35M
12w	3000k	1565	350	1,8	23013WPN.12.30M	23013WPN.12.31M	23013WPN.12.32M	23013WPN.12.35M
18w	3000k	2190	500	1,8	23013WPN.18.30M	23013WPN.18.31M	23013WPN.18.32M	23013WPN.18.35M
25w	3000k	2990	700	1,8	23013WPN.25.30M	23013WPN.25.31M	23013WPN.25.32M	23013WPN.25.35M
9w	4000k	1185	250	1,8	23013WPN.09.40M	23013WPN.09.41M	23013WPN.09.42M	23013WPN.09.45M
12w	4000k	1645	350	1,8	23013WPN.12.40M	23013WPN.12.41M	23013WPN.12.42M	23013WPN.12.45M
18w	4000k	2300	500	1,8	23013WPN.18.40M	23013WPN.18.41M	23013WPN.18.42M	23013WPN.18.45M
25w	4000k	3140	700	1,8	23013WPN.25.40M	23013WPN.25.41M	23013WPN.25.42M	23013WPN.25.45M

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



Opties:


- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI

Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren) Life expectancy (hours)

Watt	L90B10
5	80.000
9	79.000
12	78.000
18	70.000
25	64.000



23013WPN.12.30M
12w 3000k 1565lm
ηLB 74%

melis lighting