

Marici 160-150 SPECULAR SUSPENDED


Ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<22). Zeer brede bundel (>80,0°) en hoge efficiency (max 150lm/w) met **CRI>93 (R9>83)**. Gesatineerde PS Microprisma afscherming voor extra comfort. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Round suspended LED downlight. High gloss aluminium reflector (99,9%) with specular finish (UGR<22). Extra wide beam angle (>80,0°) and high efficiency (max 150lm/w) with **CRI>93 (R9>83)**. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy. High color consistency SDCM <2. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Amperage (mA) Amperage (mA)	kg kg	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali-2 Dali-2	Casambi Casambi
5w	3000k	715	>93	150	1,8	23013WPN.05.30	23013WPN.05.31	23013WPN.05.32	23013WPN.05.35
9w	3000k	1187	>93	250	1,8	23013WPN.09.30	23013WPN.09.31	23013WPN.09.32	23013WPN.09.35
12w	3000k	1646	>93	350	1,8	23013WPN.12.30	23013WPN.12.31	23013WPN.12.32	23013WPN.12.35
18w	3000k	2316	>93	500	1,8	23013WPN.18.30	23013WPN.18.31	23013WPN.18.32	23013WPN.18.35
26w	3000k	3166	>93	700	1,8	23013WPN.26.30	23013WPN.26.31	23013WPN.26.32	23013WPN.26.35
5w	4000k	715	>93	150	1,8	23013WPN.05.40	23013WPN.05.41	23013WPN.05.42	23013WPN.05.45
9w	4000k	1187	>93	250	1,8	23013WPN.09.40	23013WPN.09.41	23013WPN.09.42	23013WPN.09.45
12w	4000k	1646	>93	350	1,8	23013WPN.12.40	23013WPN.12.41	23013WPN.12.42	23013WPN.12.45
18w	4000k	2316	>93	500	1,8	23013WPN.18.40	23013WPN.18.41	23013WPN.18.42	23013WPN.18.45
26w	4000k	3166	>93	700	1,8	23013WPN.26.40	23013WPN.26.41	23013WPN.26.42	23013WPN.26.45

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%




PENDEL ARMATUREN SUSPENDED LUMINAIRES



- Opties:**
- Vlees, Brood of Crisp white
 - 2700k of 3500k

- Opties:**
- Meat, Bread or Crisp white
 - 2700k or 3500k



23013WPN.05.30
5w 3000k 715lm
ηLB 100%