

# Marici 160-150 SPECULAR SUSPENDED




Ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector (UGR<22). Zeer brede bundel (>80,0°) en hoge efficiency (max 125lm/w) met CRI>80. Gesatineerde PS Microprisma afscherming voor extra comfort. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round suspended LED downlight. High gloss aluminium reflector (99,9%) with specular finish (UGR<22). Extra wide beam angle (>80,0°) and high efficiency (max 125lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
9w	3000k	1125	250	1,8	23013WPN.09.30	23013WPN.09.31	23013WPN.09.32	23013WPN.09.35
12w	3000k	1565	350	1,8	23013WPN.12.30	23013WPN.12.31	23013WPN.12.32	23013WPN.12.35
18w	3000k	2190	500	1,8	23013WPN.18.30	23013WPN.18.31	23013WPN.18.32	23013WPN.18.35
25w	3000k	2990	700	1,8	23013WPN.25.30	23013WPN.25.31	23013WPN.25.32	23013WPN.25.35
9w	4000k	1185	250	1,8	23013WPN.09.40	23013WPN.09.41	23013WPN.09.42	23013WPN.09.45
12w	4000k	1645	350	1,8	23013WPN.12.40	23013WPN.12.41	23013WPN.12.42	23013WPN.12.45
18w	4000k	2300	500	1,8	23013WPN.18.40	23013WPN.18.41	23013WPN.18.42	23013WPN.18.45
25w	4000k	3140	700	1,8	23013WPN.25.40	23013WPN.25.41	23013WPN.25.42	23013WPN.25.45

\* Lichtstroom van armatuur, tolerantie van +/- 10%

\* Luminaire luminous flux, tolerance of +/- 10%



## PENDEL ARMATUREN / SUSPENDED LUMINAIRES



### Opties:


- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI

### Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI

### Levensduurverwachting (uren) Life expectancy (hours)

Watt	L90B10
5	80.000
9	79.000
12	78.000
18	70.000
25	64.000



### 23013WPN.09.30

9w 3000k 1125lm  
ηLB 74%

melis lighting