


Ronde LED pendel downlight. Voorzien van decoratieve aluminium (99,9%) witte reflector (UGR<22). Brede bundel (>68,0°) en hoge efficiency (max 116lm/w) met CRI>80. Gesatineerde PS Microprisma afscherming voor extra comfort. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Zeer geschikt als basis verlichting in gangen, kantoren, vides, kerken en moskeeën. Inclusief 3 meter snoer. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round suspended LED downlight. High gloss aluminium reflector (99,9%) with white finish (UGR<22). Wide beam angle (>68,0°) and high efficiency (max 116lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Direct connection to mains. Very suitable as general lighting in hallways, offices, high rooms like lobby's, churches and mosques. Including 3 meter cable. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
9w	3000k	1050	250	1,8	23013WPN.09.30W	23013WPN.09.31W	23013WPN.09.32W	23013WPN.09.35W
12w	3000k	1460	350	1,8	23013WPN.12.30W	23013WPN.12.31W	23013WPN.12.32W	23013WPN.12.35W
18w	3000k	2045	500	1,8	23013WPN.18.30W	23013WPN.18.31W	23013WPN.18.32W	23013WPN.18.35W
25w	3000k	2790	700	1,8	23013WPN.25.30W	23013WPN.25.31W	23013WPN.25.32W	23013WPN.25.35W
9w	4000k	1105	250	1,8	23013WPN.09.40W	23013WPN.09.41W	23013WPN.09.42W	23013WPN.09.45W
12w	4000k	1535	350	1,8	23013WPN.12.40W	23013WPN.12.41W	23013WPN.12.42W	23013WPN.12.45W
18w	4000k	2145	500	1,8	23013WPN.18.40W	23013WPN.18.41W	23013WPN.18.42W	23013WPN.18.45W
25w	4000k	2930	700	1,8	23013WPN.25.40W	23013WPN.25.41W	23013WPN.25.42W	23013WPN.25.45W

\* Lichtstroom van armatuur, tolerantie van +/- 10%

\* Luminaire luminous flux, tolerance of +/- 10%




#### Opties:

- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI

#### Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
5	80.000
9	79.000
12	78.000
18	70.000
25	64.000



**23013WPN.18.40W**  
18w 4000k 2145lm  
ηLB 69%