

Marici 160-150 Specular Track



Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van decoratieve aluminium (99,9%) hoogglans reflector. Gesatineerde PS Microprisma afscherming voor extra comfort (UGR<22). Zeer geschikt als basis verlichting in gangen of kantoren. Zeer brede bundel (>80,0°) en hoge efficiency (max 150lm/w) met **CRI>93 (R9>83)**. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting. Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.


Round LED downlight with adapter for 3-phase track systems. High gloss aluminium reflector (99,9%) with specular finish (UGR<22). Extra wide beam angle (>80,0°) and high efficiency (max 150lm/w) with **CRI>93 (R9>83)**. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy. High color consistency SDCM <2. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	CRI CRI	Amperage (mA) Amperage (mA)	kg kg	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali-2 Dali-2	Casambi Casambi
5w	3000k	715	>93	150	1,6	23013WT.05.30	23013WT.05.31	23013WT.05.32	23013WT.05.35
9w	3000k	1187	>93	250	1,6	23013WT.09.30	23013WT.09.31	23013WT.09.32	23013WT.09.35
12w	3000k	1646	>93	350	1,6	23013WT.12.30	23013WT.12.31	23013WT.12.32	23013WT.12.35
18w	3000k	2316	>93	500	1,6	23013WT.18.30	23013WT.18.31	23013WT.18.32	23013WT.18.35
26w	3000k	3166	>93	700	1,6	23013WT.26.30	23013WT.26.31	23013WT.26.32	23013WT.26.35

5w	4000k	715	>93	150	1,6	23013WT.05.40	23013WT.05.41	23013WT.05.42	23013WT.05.45
9w	4000k	1187	>93	250	1,6	23013WT.09.40	23013WT.09.41	23013WT.09.42	23013WT.09.45
12w	4000k	1646	>93	350	1,6	23013WT.12.40	23013WT.12.41	23013WT.12.42	23013WT.12.45
18w	4000k	2316	>93	500	1,6	23013WT.18.40	23013WT.18.41	23013WT.18.42	23013WT.18.45
26w	4000k	3166	>93	700	1,6	23013WT.26.40	23013WT.26.41	23013WT.26.42	23013WT.26.45

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



TRACK SYSTEEM TRACK SYSTEM




Accessoires:
- 3-fase rails en connectors

Opties:
- Vlees, Brood of Crisp white
(2700k, 3000k of 3500k)

Accessories:
- 3-phase tracks and connectors

Opties:
- Meat, Bread or Crisp white
- (2700k, 3000k or 3500k)



23013WT.05.30

5w 715lm 3000K
ηLB 100%