

Marici 160-150 White Track



TRACK SYSTEEM TRACK SYSTEM


Ronde LED downlight met adapter voor 3-fase rail systemen. Voorzien van decoratieve aluminium (99,9%) wit gelakte reflector (UGR<22) met brede uitstraling (>68°) en hoge efficiency (max 116lm/w) met CRI>80. Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting (50.000 uur L90B10). Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with adapter for 3-phase track systems. White painted aluminium reflector (99,9%) (UGR<22) with wide beam angle (>68°) and high efficiency (max 116lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver. Direct connection to 220-240VAC. Low maintenance and high life expectancy (50.000 hours L90B10). Colour stability, Mac Adam <3. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Artikel nr. Article no.	Dali Dali	Casambi Casambi
9w	3000k	1050	250	1,6	23013WT.09.30W	23013WT.09.32W	23013WT.09.35W
12w	3000k	1460	350	1,6	23013WT.12.30W	23013WT.12.32W	23013WT.12.35W
18w	3000k	2045	500	1,6	23013WT.18.30W	23013WT.18.32W	23013WT.18.35W
25w	3000k	2790	700	1,6	23013WT.25.30W	23013WT.25.32W	23013WT.25.35W
9w	4000k	1105	250	1,6	23013WT.09.40W	23013WT.09.42W	23013WT.09.45W
12w	4000k	1535	350	1,6	23013WT.12.40W	23013WT.12.42W	23013WT.12.45W
18w	4000k	2145	500	1,6	23013WT.18.40W	23013WT.18.42W	23013WT.18.45W
25w	4000k	2930	700	1,6	23013WT.25.40W	23013WT.25.42W	23013WT.25.45W

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



Accessoires:

- 3-fase rails en connectors

Opties:

- Vlees, Brood of Crisp white
(2700k, 3000k of 3500k)
- 90CRI of 97CRI


Accessories:

- 3-phase tracks and connectors

Opties:

- Meat, Bread or Crisp white
(2700k, 3000k or 3500k)
- 90CRI or 97CRI

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
9	79.000
12	78.000
18	70.000
25	64.000



23013WT.18.40W
18w 4000k 2145lm
ηLB 69%

melis lighting