Marici 160-150 White

PF>0,95 IP43

Ronde LED opbouw downlight. Voorzien van decoratieve aluminium (99,9%) wit gelakte reflector (UGR<22) met brede uitstraling (>68°) en hoge efficiency (max 116lm/w) met CRI>80.Gesatineerde PS Microprisma afscherming voor extra comfort. Zeer geschikt als basis verlichting in gangen of kantoren. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver met mogelijkheid tot doorlussen. Directe aansluiting op 220-240VAC. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round surface mounted LED downlight. White painted aluminium reflector (99,9%) (UGR<22) with wide beam angle (>68°) and high efficiency (max 116lm/w) with CRI>80. Satinated PS Microprism diffuser for high comfort. White painted steel body (RAL9003). Very suitable as general lighting in hallways and offices. Delivered including internal driver with possibility for through-wiring. Direct connection to 220-240VAC. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Five years warranty.

Wattage Watts	**Kleur** Colour	**Lumen*** Lumen*	**Amperage (mA)** Amperage (mA)	**kg** kg	**Artikel nr.** Article no.	**Dimbaar (1-10V)** Dimmable (1-10V)	**Dali** Dali	**Casambi** Casambi
5w	3000k	585	150	1,6	23013WPB.05.30W	23013WPB.05.31W	23013WPB.05.32W	23013WPB.05.35W
9w	3000k	1050	250	1,6	23013WPB.09.30W	23013WPB.09.31W	23013WPB.09.32W	23013WPB.09.35W
12w	3000k	1460	350	1,6	23013WPB.12.30W	23013WPB.12.31W	23013WPB.12.32W	23013WPB.12.35W
18w	3000k	2045	500	1,6	23013WPB.18.30W	23013WPB.18.31W	23013WPB.18.32W	23013WPB.18.35W
25w	3000k	2790	700	1,6	23013WPB.25.30W	23013WPB.25.31W	23013WPB.25.32W	23013WPB.25.35W
5w	4000k	615	150	1,6	23013WPB.05.40W	23013WPB.05.41W	23013WPB.05.42W	23013WPB.05.45W
9w	4000k	1105	250	1,6	23013WPB.09.40W	23013WPB.09.41W	23013WPB.09.42W	23013WPB.09.45W
12w	4000k	1535	350	1,6	23013WPB.12.40W	23013WPB.12.41W	23013WPB.12.42W	23013WPB.12.45W
18w	4000k	2145	500	1,6	23013WPB.18.40W	23013WPB.18.41W	23013WPB.18.42W	23013WPB.18.45W
25w	4000k	2930	700	1,6	23013WPB.25.40W	23013WPB.25.41W	23013WPB.25.42W	23013WPB.25.45W

* Lichtstroom van armatuur, tolerantie van +/- 10%

** Luminaire luminous flux, tolerance of +/- 10%*



OPBOUW DOWNLIGHTS

SURFACE MOUNTED DOWNLIGHTS

Opties:
- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI
- Schuinstelling voor aflopende plafonds op aanvraag
- Andere RAL kleur

Opties:
- *Meat, Bread or Crisp white (2700k or 3500k)*
- *90CRI or 97CRI*
- *Diagonal attachment for sloped ceilings on request*
- *Different RAL Colour*

Levensduurverwachting (uren) *Life expectancy (hours)*	
Watt	**L90B10**
5	80.000
9	79.000
12	78.000
18	70.000
25	64.000



23013WPB.18.40W
18w 4000k 2145lm
ηLB 69%

melis lighting