Marici 205-190 Darklight Track


Ronde LED opbouw downlight met 3-fase adapter voor rail systemen. Voorzien van trompetvormige darklight reflector van 99,98% hoogglans aluminium met brede bundel (>77°) en hoge efficiency (max 177lm/w) met **CRI>93 (R9>88)**. Zeer lage verblinding (UGR<19, 9-18w) door uniek darklight reflector ontwerp. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting (L90B10 180.000 uur). Hoge kleurconsistentie SDCM <2. Vijf jaar garantie.

Round LED surface mounted downlight with 3-phase adapter for track systems.Trumpet shaped darklight reflector made of 99,98% specular or aluminium with wide beam angle (>77°) with high efficiency (max 177lm/w) and **CRI>93 (R9>88)**. *Very low glare (UGR<19, 9-18w) due to unique darklight reflector design. White painted steel body (RAL9003). Delivered including internal driver. Direct connection to mains. Low maintenance and high life expectancy (L90B10 180.000 hours). High color consistency SDCM <2. Five years warranty.*

Wattage Watts	**Kleur** Colour	**Lumen*** Lumen*	**Amperage (mA)** Amperage (mA)	**kg** kg	**Noodvoorz. (u)** Emergency (h)	**Artikel nr.** Article no.	**Dimbaar (1-10V)** Dimmable (1-10V)	**Dali-2** Dali-2	**Casambi** Casambi
5w	3000k	841	150	2,8	1	62020WTS.00.DK	62020WTS.01.DK	62020WTS.02.DK	62020WTS.05.DK
8w	3000k	1395	250	2,8	1	62020WT.00.DK	62020WT.01.DK	62020WT.02.DK	62020WT.05.DK
12w	3000k	1935	350	2,8	1	62006WT.00.DK	62006WT.01.DK	62006WT.02.DK	62006WT.05.DK
17w	3000k	2723	500	2,8	1	62017WT.00.DK	62017WT.01.DK	62017WT.02.DK	62017WT.05.DK
25w	3000k	3723	700	2,8	1	62010WT.00.DK	62010WT.01.DK	62010WT.02.DK	62010WT.05.DK
33w	3000k	4671	900	2,8	1	62015WT.00.DK	62015WT.01.DK	62015WT.02.DK	62015WT.05.DK
39w	3000k	5313	1050	2,8	1	62013WT.00.DK	62013WT.01.DK	62013WT.02.DK	62013WT.05.DK
5w	4000k	841	150	2,8	1	62021WTS.00.DK	62021WTS.01.DK	62021WTS.02.DK	62021WTS.05.DK
8w	4000k	1395	250	2,8	1	62021WT.00.DK	62021WT.01.DK	62021WT.02.DK	62021WT.05.DK
12w	4000k	1935	350	2,8	1	62007WT.00.DK	62007WT.01.DK	62007WT.02.DK	62007WT.05.DK
17w	4000k	2723	500	2,8	1	62018WT.00.DK	62018WT.01.DK	62018WT.02.DK	62018WT.05.DK
25w	4000k	3723	700	2,8	1	62012WT.00.DK	62012WT.01.DK	62012WT.02.DK	62012WT.05.DK
33w	4000k	4671	900	2,8	1	62016WT.00.DK	62016WT.01.DK	62016WT.02.DK	62016WT.05.DK
39w	4000k	5313	1050	2,8	1	62014WT.00.DK	62014WT.01.DK	62014WT.02.DK	62014WT.05.DK

* Lichtstroom van armatuur, tolerantie van +/- 10%

* *Luminaire luminous flux, tolerance of +/- 10%*







TRACK SYSTEEM *TRACK SYSTEM*




Accessoires:
- 3-fase rails en connectors

Opties:
- 2700k

Accessories:
- *3-phase tracks and connectors*

Opties:
- 2700k



62020WTS.00.DK
5w 3000k 841lm
ηLB 100%

melis lighting