

Marici 205-190 Darklight Track




Ronde LED opbouw downlight met 3-fase adapter voor rail systemen. Voorzien van trompetvormige darklight reflector van 99,98% hoogglans aluminium met brede bundel (>77°) en hoge efficiency (max 142lm/w) met CRI>80. Zeer lage verblinding (UGR<19, 9-18w) door uniek darklight reflector ontwerp (CRI>80). Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver. Directe aansluiting op netspanning. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED surface mounted downlight with 3-phase adapter for track systems. Trumpet shaped darklight reflector made of 99,98% specular or aluminium with wide beam angle (>77°) with high efficiency (max 142lm/w) and CRI>80. Very low glare (UGR<19, 9-18w) due to unique darklight reflector design (CRI>80). White painted steel body (RAL9003). Delivered including internal driver. Direct connection to mains. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Fast and easy mounting. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dali Dali	Casambi Casambi
9w	3000k	1277	250	2,8	1	62020WT.00.DK	62020WT.02.DK	62020WT.05.DK
12w	3000k	1777	350	2,8	1	62006WT.00.DK	62006WT.02.DK	62006WT.05.DK
18w	3000k	2486	500	2,8	1	62017WT.00.DK	62017WT.02.DK	62017WT.05.DK
25w	3000k	3395	700	2,8	1	62010WT.00.DK	62010WT.02.DK	62010WT.05.DK
33w	3000k	4248	900	2,8	1	62015WT.00.DK	62015WT.02.DK	62015WT.05.DK
9w	4000k	1344	250	2,8	1	62021WT.00.DK	62021WT.02.DK	62021WT.05.DK
12w	4000k	1869	350	2,8	1	62007WT.00.DK	62007WT.02.DK	62007WT.05.DK
18w	4000k	2612	500	2,8	1	62018WT.00.DK	62018WT.02.DK	62018WT.05.DK
25w	4000k	3566	700	2,8	1	62012WT.00.DK	62012WT.02.DK	62012WT.05.DK
33w	4000k	4460	900	2,8	1	62016WT.00.DK	62016WT.02.DK	62016WT.05.DK

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



TRACK SYSTEEM TRACK SYSTEM



Accessoires:

- 3-fase rails en connectors

Opties:

- 2700k
- 90CRI of 97CRI


Accessoires:

- 3-phase tracks and connectors

Opties:

- 2700k
- 90CRI or 97CRI

Levensduurverwachting (uren) Life expectancy (hours)	
Watt	L90B10
9	79.000
12	78.000
18	70.000
25	64.000
33	57.000



62007WT.00.DK

12w 4000k 1869lm
ηLB 84%

melis lighting