

Marici 205-190 Darklight



Ronde LED opbouw downlight. Voorzien van trompetvormige darklight reflector van 99,98% hoogglans aluminium met brede bundel (>77°) en hoge efficiency (max 142lm/w) met CRI>80. Zeer lage verblinding (UGR<19, 9-18w) en minimale helderheid door uniek darklight reflector ontwerp. Wit gelakte (RAL 9003) stalen behuizing. Wordt geleverd inclusief interne driver met mogelijkheid tot doorlussen. Directe aansluiting op 220-240VAC. Snelle en eenvoudige montage. Onderhoudsarm en hoge levensduurverwachting. Kleur stabiliteit, Mac Adam <3. Vijf jaar garantie.

Round LED downlight with shallow build-in height (99mm). Trumpet shaped darklight reflector made of 99,98% specular aluminium with wide beam angle (>77°) with high efficiency (max 142lm/w) and CRI>80. Very low glare (UGR<19, 9-18w) and minimal brightness due to unique darklight reflector design. White painted steel body (RAL9003). Delivered including internal driver with possibility for through-wiring. Direct connection to 220-240VAC. Low maintenance and high life expectancy. Colour stability, Mac Adam <3. Five years warranty.

Wattage Watts	Kleur Colour	Lumen* Lumen*	Amperage (mA) Amperage (mA)	kg kg	Noodvoorz. (u) Emergency (h)	Artikel nr. Article no.	Dimbaar (1-10V) Dimmable (1-10V)	Dali Dali	Casambi Casambi
9w	3000k	1277	250	2,8	1	62020WPB.00.DK	62020WPB.01.DK	62020WPB.02.DK	62020WPB.05.DK
12w	3000k	1777	350	2,8	1	62006WPB.00.DK	62006WPB.01.DK	62006WPB.02.DK	62006WPB.05.DK
18w	3000k	2486	500	2,8	1	62017WPB.00.DK	62017WPB.01.DK	62017WPB.02.DK	62017WPB.05.DK
25w	3000k	3395	700	2,8	1	62010WPB.00.DK	62010WPB.01.DK	62010WPB.02.DK	62010WPB.05.DK
33w	3000k	4248	900	2,8	1	62015WPB.00.DK	62015WPB.01.DK	62015WPB.02.DK	62015WPB.05.DK
9w	4000k	1344	250	2,8	1	62021WPB.00.DK	62021WPB.01.DK	62021WPB.02.DK	62021WPB.05.DK
12w	4000k	1869	350	2,8	1	62007WPB.00.DK	62007WPB.01.DK	62007WPB.02.DK	62007WPB.05.DK
18w	4000k	2612	500	2,8	1	62018WPB.00.DK	62018WPB.01.DK	62018WPB.02.DK	62018WPB.05.DK
25w	4000k	3566	700	2,8	1	62012WPB.00.DK	62012WPB.01.DK	62012WPB.02.DK	62012WPB.05.DK
33w	4000k	4460	900	2,8	1	62016WPB.00.DK	62016WPB.01.DK	62016WPB.02.DK	62016WPB.05.DK

* Lichtstroom van armatuur, tolerantie van +/- 10%

* Luminaire luminous flux, tolerance of +/- 10%



OPBOUW DOWNLIGHTS SURFACE MOUNTED DOWNLIGHTS



Opties:


- Vlees, Brood of Crisp white (2700k of 3500k)
- 90CRI of 97CRI
- Schuinstelling voor aflopende plafonds op aanvraag
- Andere RAL kleur

Opties:

- Meat, Bread or Crisp white (2700k or 3500k)
- 90CRI or 97CRI
- Diagonal attachment for sloped ceilings on request
- Different RAL Colour

Levensduurverwachting (uren) Life expectancy (hours)

Watt	L90B10
9	79.000
12	78.000
18	70.000
25	64.000
33	57.000



62007WPB.00.DK
12w 4000k 1869lm
ηLB 84,0%

melis lighting